

Parker E-z-mate Industrial Interchange Couplers

E-z-mate couplings combine push-to-connect, exhaust-style action with a self-locking valve sleeve to guard against accidental disconnection. Simply follow the direction of the on-off arrow stamped on the yellow chromate valve sleeve. Valve sleeve acts as an integral shut-off valve that allows connection and disconnection at zero pressure. When the sleeve is moved to shut off air flow, it automatically vents downstream allowing for disconnection at zero pressure and eliminating the risk of hose whip.

Features:

- pressure rating: **300 PSI**
- temperature range (standard seals): **-40°F to +250°F**
- meets ISO 4414 requirements for a controlled pressure release system
- not recommended for vacuum service 

Female Pipe Thread

| Body Size | Female NPT | Material | Flow Rating at 100 PSI | Part # | Price/E | Opt Qty |
|-----------|------------|----------|------------------------|-----------------|----------------|---------|
| 1/4" | 1/4"-18 | steel | 37 CFM | DC20SE | \$54.00 | 10 |
| 1/4" | 3/8"-18 | steel | 37 CFM | DC2023SE | 58.20 | 10 |
| 3/8" | 3/8"-18 | steel | 70 CFM | DC26SE | 65.00 | 5 |
| 3/8" | 1/2"-14 | steel | 70 CFM | DC2624SE | 71.10 | 5 |
| 1/2" | 1/2"-14 | steel | 150 CFM | DC10SE | 76.50 | 5 |
| 1/2" | 3/4"-14 | steel | 150 CFM | DC1026SE | 84.15 | 5 |
| 3/4" | 3/4"-14 | steel | 200 CFM | DC7026SE | 112.50 | 5 |
| 3/4" | 1"-11-1/2 | steel | 200 CFM | DC7028SE | 133.00 | 5 |



Male Pipe Thread

| Body Size | Male NPT | Material | Flow Rating at 100 PSI | Part # | Price/E | Opt Qty |
|-----------|----------|----------|------------------------|-----------------|----------------|---------|
| 1/4" | 1/4"-18 | steel | 37 CFM | DC21SE | \$62.00 | 10 |
| 1/4" | 3/8"-18 | steel | 37 CFM | DC2103SE | 72.50 | 10 |
| 3/8" | 3/8"-18 | steel | 70 CFM | DC25SE | 78.75 | 5 |
| 1/2" | 1/2"-14 | steel | 150 CFM | DC9SE | 83.70 | 5 |
| 3/4" | 3/4"-14 | steel | 200 CFM | DC7106SE | 151.80 | 5 |



Standard Hose Barb

| Body Size | Hose ID | Material | Flow Rating at 100 PSI | Part # | Price/E | Opt Qty |
|-----------|---------|----------|------------------------|-----------------|----------------|---------|
| 1/4" | 1/4" | steel | 37 CFM | DC2042SE | \$74.40 | 10 |
| 1/4" | 3/8" | steel | 37 CFM | DC2044SE | 77.75 | 10 |
| 3/8" | 3/8" | steel | 70 CFM | DC2644SE | 83.00 | 5 |
| 1/2" | 1/2" | steel | 150 CFM | DC1045SE | 87.50 | 5 |



Push-Lock Hose Barb

| Body Size | Hose ID | Material | Flow Rating at 100 PSI | Part # | Price/E | Opt Qty |
|-----------|---------|----------|------------------------|------------------|----------------|---------|
| 1/4" | 1/4" | steel | 37 CFM | DC2042LSE | \$89.25 | 10 |
| 1/4" | 3/8" | steel | 37 CFM | DC2044LSE | 75.25 | 10 |
| 3/8" | 3/8" | steel | 70 CFM | DC2644LSE | 80.25 | 5 |
| 1/2" | 1/2" | steel | 150 CFM | DC1045LSE | 87.35 | 5 |



Legris Automatic Industrial Interchange Safety Couplers

Applications:

- suited for numerous installations including: pneumatic tools, blow guns, pneumatic automotive equipment

Features:

- composite, non-marring body
- 1/4" body size ensures excellent flow and total security due to disconnection in two steps
- compatible with industrial interchange plugs



1. vents plug side



2. disconnects



male NPT straight body



female NPT straight body

| Body Size | NPT Size | Part # | Price/E |
|-----------|----------|------------------|----------------|
| 1/4" | 1/4" | 9405U0614 | \$39.00 |
| 1/4" | 3/8" | 9405U0618 | 43.75 |

| Body Size | NPT Size | Part # | Price/E |
|-----------|----------|------------------|----------------|
| 1/4" | 1/4" | 9415U0614 | \$39.00 |
| 1/4" | 3/8" | 9415U0618 | 43.75 |