

Push-On Fittings



Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only. No hose clamps or ferrules are needed. Push-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

37° JIC Hose Barb Fittings male 37° JIC x push-on hose barb

Hose ID	Tube OD	Male UNF	Brass Part #	Price/E	Opt Qty
1/4"	1/4"	7/16"-20	286-0407	\$3.80	100
1/4"	5/16"	1/2"-20	286-0408	7.65	50
1/4"	3/8"	9/16"-18	286-0409	5.65	100
3/8"	3/8"	9/16"-18	286-0609	5.50	50
1/2"	1/2"	3/4"-16	286-0812	7.37	25
5/8"	5/8"	7/8"-14	286-1014	9.31	25
3/4"	3/4"	1-1/16"-12	286-1217 ¹	14.25	10

¹ UN thread



female 37° JIC swivel x push-on hose barb

Hose ID	Tube OD	Female UNF	Brass Part #	Price/E	Opt Qty
1/4"	3/8"	9/16"-18	288-0409	\$5.21	50
5/16"	3/8"	9/16"-18	288-0509	6.21	50
3/8"	3/8"	9/16"-18	288-0609	5.21	50
1/2"	3/8"	9/16"-18	288-0809	7.70	25
3/4"	3/4"	1-1/16"-12	288-1217 ¹	13.49	10
1"	1"	1-5/16"-12	288-1621 ¹	30.83	10

¹ UN thread



Hose ID	Tube OD	Female UNF	303 SS Part #	Price/E	Opt Qty
3/8"	3/4"	9/16"-18	288-0609SS	\$62.70	50
3/4"	3/4"	1-1/16"-12	288-1217SS	111.85	10
1"	1"	1-5/16"-12	288-1621SS	96.17	10

female 45°SAE / 37°JIC swivel x push-on hose barb (dual angle seat)

Hose ID	Tube OD	Female UNF	Brass Part #	Price/E	Opt Qty
1/4"	1/4"	7/16"-20	287-0407	\$3.96	100
1/4"	5/16"	1/2"-20	287-0408	4.91	100
3/8"	5/16"	1/2"-20	287-0608	7.34	25
3/8"	1/2"	3/4"-16	287-0612	6.30	25
1/2"	1/2"	3/4"-16	287-0812	6.36	25
1/2"	5/8"	7/8"-14	287-0814	9.11	25
5/8"	5/8"	7/8"-14	287-1014	9.71	25



Hose ID	Tube OD	Female UNF	303 SS Part #	Price/E	Opt Qty
1/4"	1/4"	7/16"-20	287-0407SS	\$46.95	100
1/2"	1/2"	3/4"-16	287-0812SS	65.45	25

female 37° JIC/45° SAE swivel x push-on 90° elbow

Hose ID	Tube OD	Female UNF	Plated Steel Part #	Price/E	Opt Qty
1/4"	1/4"	7/16"-20	289-0407 ³	\$27.00	25
1/4"	1/4"	7/16"-20	289-0407SAE ¹	35.72	25
3/8"	3/8"	9/16"-18	289-0609 ³	25.35	25
3/8"	3/8"	5/8"-18	289-0610SAE ¹	36.45	25
1/2"	1/2"	3/4"-16	289-0812 ³	31.10	10
3/4"	3/4"	1-1/16"-12	289-1217 ^{2,3}	84.52	5

¹ notch in nut for SAE identification

² UN thread

³ JIC only, may substitute dual angle

