

HTM Hi Torque Clamps

Features:

- withstands more than three times the SAE torque requirements for worm-driven clamps
- eight screw threads are engaged in the band simultaneously for incredible torquing drive (over 150 in. lbs.), sealing pressure and vibration resistance
- slotted hex head screw design

Material:

- band and housing: 300 series half hard stainless
- screw: 410 stainless steel screw



style HTM

Band Width	Hose OD		Stainless Steel		Opt Qty
	from	to	Part #	Price/E	
5/8"	1 1/4"	2 1/8"	HTM200	\$5.05	10
	1 3/4"	2 5/8"	HTM250	5.10	10
	2 1/4"	3 1/8"	HTM300	5.30	10
	2 3/4"	3 5/8"	HTM350	5.40	10
	3 1/2"	4 1/8"	HTM400	5.55	10
	3 3/4"	4 5/8"	HTM450	5.70	10
	4 1/4"	5 1/8"	HTM500	5.90	10
	4 3/4"	5 5/8"	HTM550	6.30	10
	5 1/4"	6 1/8"	HTM600	6.45	10
	5 3/4"	6 5/8"	HTM650	6.55	10
	6 1/4"	7 1/8"	HTM700	6.75	10
	6 3/4"	7 5/8"	HTM750	7.30	10
	7 1/4"	8 1/8"	HTM800	7.45	10
	7 3/4"	8 5/8"	HTM850	7.60	10
	8 1/4"	9 1/8"	HTM900	7.80	10

extended range sizes



style HP

Band Width	Hose OD		Stainless Steel	
	from	to	Part #	Price/E
5/8"	1 1/4"	2 5/8"	HP2	\$5.10
	2 1/8"	4 1/8"	HP3	5.55
	4"	6 1/8"	HP4	6.45
	6 1/8"	9 1/8"	HP5	7.80

Constant Torque Clamps

Features:

- A patented Belleville spring mechanism permits the clamp to automatically increase or decrease its own diameter due to changes in operational or environmental temperatures.
- 3/8" hex, carbon steel screw
- 5/8" wide 304 stainless steel band



Band Width	Hose OD		Part #	Price/E	Hose OD		Part #	Price/E
	from	to			from	to		
5/8"	1"	1 3/4"	CT175L	\$19.30	5 1/4"	6 1/8"	CT600L	\$21.75
	1 1/4"	2 1/8"	CT200L	19.30	5 3/4"	6 5/8"	CT650L	21.75
	1 3/4"	2 5/8"	CT250L	19.50	6 1/4"	7 1/8"	CT700L	22.25
	2 1/4"	3 1/8"	CT300L	19.80	6 3/4"	7 5/8"	CT750L	23.25
	2 3/4"	3 5/8"	CT350L	20.00	7 1/4"	8 1/8"	CT800L	23.50
	3 1/4"	4 1/8"	CT400L	20.25	7 3/4"	8 5/8"	CT850L	23.75
	3 3/4"	4 5/8"	CT450L	20.50	8 1/4"	9 1/8"	CT900L	24.00
	4 1/4"	5 1/8"	CT500L	20.75	8 3/4"	9 5/8"	CT950L	24.50
	4 3/4"	5 5/8"	CT550L	21.50	--	--	--	--