

Two Way Male Outlet - Roof Connections 

26-294 / 26-296

**Features:**

- Used to create roof connections, fire pump test connections, wall hydrants or sidewalk (free standing) hydrants
- provides 250 GPM minimum per outlet
- U/L listed
- maximum operating pressure: **175 PSI** at 70°F (21°C)

**back inlet**


| Pipe | (2) Outlets Male | Cast Brass Part #           | Price           | Wt. Lbs. |
|------|------------------|-----------------------------|-----------------|----------|
| 4"   | 2½" NPT          | <b>IRC4025</b>              | <b>\$207.20</b> | 9.50     |
|      | 2½" NPT          | <b>FRC4025-D</b>            | <b>443.85</b>   | 9.50     |
|      | 2½" NST (NH)     | <b>IRC4025F</b>             | <b>207.20</b>   | 9.50     |
|      | 2½" NST (NH)     | <b>FRC4025F-D</b>           | <b>443.85</b>   | 9.50     |
|      | 2½" CT           | <b>FRC4025</b> <sup>1</sup> | <b>POR</b>      | 9.50     |
| 6"   | 2½" NPT          | <b>FRC6025</b>              | <b>657.10</b>   | 14.25    |
|      | 2½" NST (NH)     | <b>FRC6025F</b>             | <b>657.10</b>   | 14.25    |
|      | 2½" NYFD         | <b>FRC6025NYFD</b>          | <b>690.00</b>   | 14.25    |
|      | 2½" CT           | <b>FRC6025</b> <sup>1</sup> | <b>POR</b>      | 14.25    |

<sup>1</sup> Customer Thread (*must specify*) refer to legend on page 566

| Groove Size | (2) Outlets Male | Cast Brass Part # | Price           | Wt. Lbs. |
|-------------|------------------|-------------------|-----------------|----------|
| 4"          | 2½" MNPT         | <b>IRC4025G</b>   | <b>\$213.00</b> | 7.05     |
| 4"          | 2½" MNST         | <b>IRC4025GF</b>  | <b>213.00</b>   | 7.05     |

**Dimensions**

| Size           | A       | B       | C      |
|----------------|---------|---------|--------|
| 4" x 2½" x 2½" | 7-7/8"  | 5-3/16" | 5-1/4" |
| 6" x 2½" x 2½" | 8-3/16" | 6-3/8"  | 7-5/8" |

**90° bottom inlet**

26-296

| Pipe Size | (2) Outlets Male | Cast Brass Part #             | Price           | Wt. Lbs. |
|-----------|------------------|-------------------------------|-----------------|----------|
| 4"        | 2½" NPT          | <b>90IRC4025</b>              | <b>\$230.00</b> | 6.00     |
|           | 2½" NPT          | <b>90FRC4025-D</b>            | <b>443.35</b>   | 8.25     |
|           | 2½" NST (NH)     | <b>90IRC4025F</b>             | <b>230.00</b>   | 6.00     |
|           | 2½" NST (NH)     | <b>90FRC4025F-D</b>           | <b>443.35</b>   | 8.25     |
|           | 2½" CT           | <b>90FRC4025</b> <sup>1</sup> | <b>POR</b>      | 8.25     |
| 6"        | 2½" NPT          | <b>90FRC6025</b>              | <b>620.00</b>   | 15.80    |
|           | 2½" NST (NH)     | <b>90FRC6025F</b>             | <b>620.00</b>   | 15.80    |
|           | 2½" CT           | <b>90FRC6025</b> <sup>1</sup> | <b>POR</b>      | 15.80    |
|           | 2½" CT           | <b>FRC6025</b> <sup>1</sup>   | <b>POR</b>      | 14.25    |

<sup>1</sup> Customer Thread (*must specify*) refer to legend on page 566

| Groove Size | (2) Outlets Male | Cast Brass Part #  | Price           | Wt. Lbs. |
|-------------|------------------|--------------------|-----------------|----------|
| 4"          | 2½" MNPT         | <b>90IRC4025G</b>  | <b>\$230.00</b> | 7.05     |
| 4"          | 2½" MNST         | <b>90IRC4025GF</b> | <b>230.00</b>   | 7.05     |

**Dimensions**

| Size           | A   | B   | C   | D   |
|----------------|-----|-----|-----|-----|
| 4" x 2½" x 2½" | 7½" | 6¾" | 5⅞" | 4½" |
| 6" x 2½" x 2½" | 9"  | 8½" | 7½" | 5"  |

**P**