


NOTE: 286T HAS 6 MTG. HOLES, USING 254T AND 256T LOCATIONS

FRAME DESIGN	"C"	"BV"
284TS	22.17	9.11
286TS	23.62	9.83

		TOLERANCES UNLESS SPECIFIED		 ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN	JJK 04/05/99			
		DEC.	INCHES		CHK	PG 04/07/99	APPD		
		.X	±.1	TITLE OUTLINE 280TS FRAME DRIP PROOF - RIGID NEW CON-BOX		SCALE 1=4			
		.XX	±.03			REF			
		.XXX	±.005			FMF			
A	REVISED TO NEW BORDER FORMAT	DWF	12/14/01	MAT'L	CAST IRON				
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH	PREV		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	Drawing6	SIZE	DRAWING NO.	REV.
				DIST	B	169553-60	A		