

## 1-GANG BLANK AND DEVICE COVERS

2-3/4" W x 4-1/2" H

### Features:

- Zinc Die Cast (Except 1-BC, 1-BC-G, & 1CA-SW)
- Gasket included
- Device mounted
- Meets NEC Article 406.9 (A) for damp and wet locations (for more information visit pg. W15)

Weatherproof

Cat. No.	Description	Color (Cat. No. - Color Code)			Std. Pkg.
		Gray	Bronze	White	
<b>1-BC</b>	Aluminum Blank (Unpainted)	1-BC	-	-	50
<b>1-BC-G</b>	Heavy-Duty Galvanized Steel Blank	1-BC-G	1-BC-BR	1-BC-W	50
<b>1C-TS</b>	Toggle Switch	1C-TS	1C-TS-BR	1C-TS-W	25
<b>1C-DH</b>	Duplex/Combo. Device - Horizontal	1C-DH	1C-DH-BR	1C-DH-W	25
<b>1C-DV</b>	Duplex/Combo. Device - Vertical	1C-DV	1C-DV-BR	1C-DV-W	25
<b>1C-GH</b>	GFCI - Horizontal	1C-GH	1C-GH-BR	1C-GH-W	25
<b>1C-GV</b>	GFCI - Vertical	1C-GV	1C-GV-BR	1C-GV-W	25
<b>1C-SH</b>	Single recept. or Switch Horizontal - 1.406" Diameter	1C-SH	-	-	25
<b>1C-SV</b>	Single recept. or Switch Vertical - 1.406" Diameter	1C-SV	1C-SV-BR	1C-SV-W	25
<b>1C-PO20</b>	20A Power Outlet - 1.594" Diameter	1C-PO20	-	-	25
<b>1C-PO30</b>	30A Power Outlet - 1.750" Diameter	1C-PO30	-	-	25
<b>1C-PO40</b>	40-50A Power Outlet - 2.281" Diameter	1C-PO40	-	-	25
<b>1C-SW</b>	Lever + 15A Single-Pole Switch	1C-SW	1C-SW-BR	1C-SW-W	25
<b>1C-SW-20</b>	Lever + 20A Single-Pole Switch	1C-SW-20	-	-	25
<b>1C-SW-NS</b>	Lever Cover without Switch	1C-SW-NS	-	-	25
<b>1CA-SW</b> <small>NEW</small>	Aluminum Lever, compatible with Standard Toggle Switches	1CA-SW	1CA-SW-BR	1CA-SW-W	25
<b>G-1</b>	Universal 1-Gang Foam Gasket	G-1 (Black only)			50

