# **Push-On Fitting Tool**

#### Features:

- · cuts push-on style hose and inserts the fitting
- Built-in cutter slices through 1/4" 3/4" ID reinforced push-on hose without fraying.
- · Clamp hose into tools vice and apply light pressure on handle to drive in the fitting.
- tool has four 7/16" diameter mounting holes for bench mounting
- overall size is 13½" long x 2¾" wide x 7" height

#### **Installation Instructions:**

- 1. To cut your hose, retract the handle, place the hose in the cutter area and pull the handle.
- 2. After cutting the hose to the desired length, place the hose under the cam handle locking it in place with the hose end aligned with the appropriate mark on the label.
- 3. Place the barbed end of the fitting against the end of the hose and then pull the handle forward to complete the installation.

Size	Part #	Price/E
1/4" - 3/4"	270AT	\$1146.50



A

Caution: Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

### **Push-On Fitting Insertion Tool Blade**

Description	Part #	Price/E
replacement blade	270AT-RPLBlade	\$193.50

## **Hose Assembly Tool**

- installs 1/4", 5/16" and 3/8" hose fittings
- · lightweight, portable, comfortable cushioned grip
- · economical

Part #	Price/E
ННСІ	\$222.00



## **Yellow Lok-on Caps**

- intended for use with Lok-On (push-on style) hose only
- · No hose clamps or ferrules are needed for installation
- Properly grips push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

$\wedge$	
4	

Hose ID	Plastic		Pkg Qty
	Part #	Price/E	i ng Qiy
1/4"	2720400W	\$0.14	100
5/16"	2720500W	0.13	100
3/8"	2720600W	0.18	100
1/2"	2720800W	0.22	100
5/8"	2721000W	0.23	50
3/4"	2721200W	0.29	50
1"	2721600W	4.31	25





