

Push-On Fittings



Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only. No hose clamps or ferrules are needed. Push-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

45° SAE Hose Barb Fittings

male 45° SAE x push-on hose barb



Hose ID	Tube OD	Male UNF	Brass Part #	Price/E	Opt Qty
1/4"	1/4"	7/16"-20	282-0407	\$3.85	100
1/4"	5/16"	1/2"-20	282-0408	3.50	100
3/8"	3/8"	5/8"-18 ¹	282-0610	4.95	50
1/2"	1/2"	3/4"-16	282-0812	6.66	50
5/8"	5/8"	7/8"-14	282-1014	9.60	25
3/4"	3/4"	1-1/16"-14 ¹	282-1217	15.46	25

¹ notch in hex for SAE identification

female 45° SAE swivel x push-on hose barb



Hose ID	Tube OD	Female UNF	Brass Part #	Price/E	Opt Qty
1/4"	3/8"	5/8"-18 ¹	284-0410	\$6.30	50
5/16"	3/8"	5/8"-18 ¹	284-0510	6.44	50
3/8"	3/8"	5/8"-18 ¹	284-0610	5.05	100
3/4"	3/4"	1-1/16"-14 ¹	284-1217	13.00	25

¹ notch in hex for SAE identification

SAE Inverted Flare Fittings

male SAE swivel x push-on hose barb



Hose ID	Tube OD	Male UNF	Brass Part #	Price/E	Opt Qty
1/4"	3/16"	3/8"-24	290-0406	\$7.80	100
1/4"	1/4"	7/16"-24	290-0407 ¹	5.40	100
1/4"	5/16"	1/2"-20	290-0408	6.16	100
5/16"	5/16"	1/2"-20	290-0508	6.72	50
5/16"	3/8"	5/8"-18	290-0510	8.10	50
3/8"	5/16"	1/2"-20	290-0608	7.95	100
3/8"	3/8"	5/8"-18	290-0610	7.95	50
1/2"	1/2"	3/4"-18	290-0812 ¹	10.10	50
5/8"	5/8"	7/8"-18	290-1014 ¹	13.03	25

¹ UNS thread

rigid female SAE x push-on hose barb



Hose ID	Tube OD	Female UNF	Brass Part #	Price/E	Opt Qty
1/4"	3/16"	3/8"-24	292-0406	\$4.20	100
1/4"	1/4"	7/16"-24	292-0407 ¹	3.82	100
1/4"	5/16"	1/2"-20	292-0408	4.25	100
5/16"	5/16"	1/2"-20	292-0508	4.25	100
3/8"	5/16"	1/2"-20	292-0608	5.76	100
3/8"	3/8"	5/8"-18	292-0610	5.49	50
1/2"	1/2"	3/4"-18	292-0812 ¹	8.18	25

¹ UNS thread