

4S Deep Boxes (BSA) & 4S Covers

4" SQUARE (4S) DEEP BOXES

WELDED

2-1/8" DEEP

30.3 Cu. In.


WITH RAISED GROUND EMBOSS

Boxes with Pigtail Features:

- 10" Solid Cu. #12AWG Pigtail pre-assembled with Ground Emboss and 10-32 Ground Screw

BSA Features:

- UMI Back Support Arm installed on this box provides support for studs up to 6" deep
- An excellent choice for pre-fab applications



Adjustable Rings Features:

- For more information see Page A13


Note:

- MKO configuration revised October 2012


4" SQUARE (4S) COVERS

FLAT OR DRAWN


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SDB-50/75-PT-BSA	With Back Support Arm	8 - 1/2", 4 - 3/4"	1 - 1/2", 2 - 3/4"	24
4SDB-50/75-AB-PT-BSA	With AB, Flush, Back Support Arm	6 - 1/2", 3 - 3/4"	1 - 1/2", 2 - 3/4"	24
4SDB-MKO-PT-BSA	With Back Support Arm	8 - 1/2", 4 - MKO	1 - 1/2", 2 - MKO	24
4SDB-MKO-AB-PT-BSA	With AB, Flush, Back Support Arm	6 - 1/2", 3 - MKO	1 - 1/2", 2 - MKO	24
4SDB-MKO-AR1G	AB, Flush, Back Support Arm w/ 4SA1RG	6 - 1/2", 3 - MKO	1 - 1/2", 2 - MKO	24
4SDB-MKO-AR2G	AB, Flush, Back Support Arm w/ 4SA2RG	6 - 1/2", 3 - MKO	1 - 1/2", 2 - MKO	24




4SDB-50/75-PT-BSA




4SDB-50/75-AB-PT-BSA




4SDB-MKO-PT-BSA



4SDB-MKO-AB-PT-BSA




4SDB-MKO-AR1G




4SDB-MKO-AR2G

Fully Assembled with Adjustable Ring, 10" Ground Pigtail & Adjustable Back Support


Cat. No.	Description	Cu. Inch	Std. Pkg.
4BC	Flat, Blank	-	50
4BCK	Flat, 1/2" KO	-	50
4BC-MKO	Flat, MKO	-	50
43000	Flat, Open, Ears 2-3/4" O.C.	-	50
43050	Raised 1/2", Open, Ears 2-3/4" O.C.	3.0	50
43058	Raised 5/8", Open, Ears 2-3/4" O.C.	4.0	50
43075	Raised 3/4", Open, Ears 2-3/4" O.C.	5.0	50
43100	Raised 1", Open, Ears 2-3/4" O.C.	6.8	25
43125	Raised 1-1/4", Open, Ears 2-3/4" O.C.	8.5	25
43150	Raised 1-1/2", Open, Ears 2-3/4" O.C.	9.7	25
43200	Raised 2", Open, Ears 2-3/4" O.C.	12.9	25




4BC




4BCK



4BC-MKO



43000



43050
43058
43075
43100
43125
43150
43200

- 600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Acceptable for use in 2-hour rated walls
- Visit www.ul.com or QCIT Guide on page W1 for more information