

5600 Series Hydraulic Quick-Connect Couplings

Features:

- two-way check valves in the plug and coupler automatically balance in flow position and provide instant shut off when disconnected
- permits fast connection and disconnection of gas or fluid lines with minimal loss of media from either end
- to connect, simply retract sleeve, insert plug, and release sleeve
- interchangeable with Aeroquip 5600, Parker 6600, and **ISO A interchange**, see Hydraulic Profile Chart on page 833
- non-valved, slotted valve and straight through units available on request



Couplers

Body Size	Female NPTF	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/8" - 27	5000	steel	56-100	\$45.25	5
1/4"	1/4" - 18	5000	steel	56-200	37.50	5
3/8"	3/8" - 18	4000	steel	56-300	45.25	5
1/2"	1/2" - 14	4000	steel	56-400	47.25	5
1/2"	3/4" - 14	4000	steel	56-600	64.50	5
3/4"	3/4" - 14	4000	steel	56-660	71.00	5
1"	1" - 11 1/2	4000	steel	56-800	90.50	5



Plugs

Body Size	Female NPTF	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/8" - 27	5000	steel	57-100	\$18.30	5
1/4"	1/4" - 18	5000	steel	57-200	16.10	5
3/8"	3/8" - 18	4000	steel	57-300	22.00	5
1/2"	1/2" - 14	4000	steel	57-400	20.00	5
1/2"	3/4" - 14	4000	steel	57-600	36.30	5
3/4"	3/4" - 14	4000	steel	57-660	37.90	5
1"	1" - 11 1/2	4000	steel	57-800	49.50	5

Dust Plugs



Body Size	Material	Part #	Price/E	Opt Qty
1/4"	rubber	56-002	\$5.30	5
3/8"	rubber	56-003	5.95	5
1/2"	rubber	56-004	5.30	5
3/4"	rubber	56-006	12.50	5
1"	rubber	56-008	15.50	5

Dust Caps



Body Size	Material	Part #	Price/E	Opt Qty
1/4"	rubber	57-002	\$5.25	5
3/8"	rubber	57-003	5.95	5
1/2"	rubber	57-004	5.35	5
3/4"	rubber	57-006	12.25	5
1"	rubber	57-008	15.20	5