



DASH	FRAME	C	BS	MOUNTING
965	213T	18.04	4.82	F1/F2
1115	213/15T	19.54	6.32	F1/F2
1240	215T	20.79	7.57	F1 ONLY

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY TO BE .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT TO BE .002 T.I.R.
 ALIGN BASE TO C-FACE MOUNTING HOLES WITHIN $\pm 1/16$ "

SPECIAL FEATURES:

- 1) SHAFT SEALS & V-RING
- 2) PLUGGED DRAIN HOLES IN FRAME & CONDUIT BOX
- 3) GASKETS THROUGHOUT
- 4) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE

		TOLERANCES UNLESS SPECIFIED		REGAL™ Regal Beloit America, Inc.		DRAWNSYED 08/21/2015					
		DEC.	INCHES			CHK AJ 08/21/2015					
		.X	±.1	TITLE		APPD					
		.XX	±.03	OUTLINE		SCALE 1=5					
01	FAN GUARD UPDATED	.XXX	±.005	210 FR. - BB - TS - TEFC - R/S		REF					
0	NEW DRAWING RELEASE	.XXXX	±.0005	MAT'L.		FMF					
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	PREV					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	038034	SIZE	DRAWING NO.	PAGE	OF	REV.
				DIST			A	038034			B