

Hydraulic Water-Blast Quick Couplings

Features:

- plug mounted sleeve guard protects against accidental disconnection
- smooth bore full-flow design ensures maximum flow with minimal pressure drop
- steel body components maximize service life by resisting the effects of brinelling and internal erosion
- heavy duty knurled sleeve with locking pin provides maximum protection against brinelling and accidental disconnection
- interchangeable with Parker WB, Aeroquip FD69, and Snap Tite 56


Couplers

Body Size	Female NPTF	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/2"	3/8" - 18	10000	steel	4EAF3	\$125.17	25
1/2"	1/2" - 14	10000	steel	4EAF4	125.17	25



Plugs

Body Size	Female NPTF	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/2"	3/8" - 18	10000	steel	EA4F3	\$27.06	25
1/2"	1/2" - 14	10000	steel	EA4F4	33.86	25



Hydraulic Suction and Return Line Hose Couplings

Application:


- designed for hydraulic suction line applications using SAE100R4 hydraulic hose

Feature:

- barbs provide easy assembly and maximum gripping action


**Stems
male NPTF**

Hose ID	Male NPTF	Plated Steel	
		Part #	Price/E
3/4"	3/4"-14	188-12	\$14.10
1"	1"-11 1/2"	188-16	33.00
1 1/4"	1 1/4"-11 1/2"	188-20	62.00
1 1/2"	1 1/2"-11 1/2"	188-24	76.00
2"	2"-11 1/2"	188-32	117.00



female SAE (JIC) 37° swivel

Hose ID	Female SAE	Plated Steel	
		Part #	Price/E
3/4"	1-1/16"-12	688-12	\$19.70
1"	1-5/16"-12	688-16	39.00
1 1/4"	1-5/8"-12	688-20	84.00
1 1/2"	1-7/8"-12	688-24	91.00
2"	2-1/2"-12	688-32	186.60



- return line clamps must be used with these fittings

Clamps

Features:



- measure hose OD accurately before ordering clamps
- Torque values for clamps are based on dry bolts. The use of lubricant on bolts will adversely effect clamp performance.
- consult Dixon when using double bolt clamps on helical wire hose

without saddles

Hose ID	Hose OD		Zinc Plated Iron		Opt Qty	Torque in ft. lbs.
	from	to	Part #	Price/E		
3/4"	1-8/64"	1-12/64"	J48	\$7.30	100	15
1"	1-40/64"	1-52/64"	DL 14	13.20	25	40
1 1/4"	1-48/64"	2-3/64"	DL20	13.25	25	27
1 1/2"	2-7/64"	2-19/64"	DL24 ¹	12.70	25	27
2"	2-20/64"	2-40/64"	DL32 ¹	13.70	25	40



¹ made from investment cast carbon steel