

TrueSeal™ Ball Valves

Valve Male Connectors



tube to male NPTF

Tube OD	Male NPTF	Nylon Part #	Price/E	Pkg Qty
1/4"	1/4"	PP4VMC4-MG	\$13.75	10
1/4"	3/8"	PP4VMC6-MG	17.60	10
3/8"	1/4"	PP6VMC4-MG	14.15	10
3/8"	3/8"	PP6VMC6-MG	14.20	10

Valve Union Connectors



tube to tube

Tube OD 1	Tube OD 2	Nylon Part #	Price/E	Pkg Qty
1/4"	1/4"	PP4VUC4-MG	\$13.15	10
3/8"	1/4"	PP4VUC6-MG	16.45	10
3/8"	3/8"	PP6VUC6-MG	14.70	10

Valve Plug-in Elbow Unions



tube to plug-in

Tube OD	Stem	Nylon Part #	Price/E	Pkg Qty
1/4"	3/8"	PP4VTEU6-MG	\$18.65	10
3/8"	3/8"	PP6VTEU6-MG	20.75	10

Valve Female Connectors



tube to female NPTF

Tube OD	Female NPTF	Nylon Part #	Price/E	Pkg Qty
1/4"	1/8"	PP4VFC2-MG	\$17.45	10
1/4"	1/4"	PP4VFC4-MG	16.75	10
1/4"	3/8"	PP4VFC6-MG	16.75	10
3/8"	1/8"	PP6VFC2-MG	18.05	10
3/8"	1/4"	PP6VFC4-MG	17.35	10
3/8"	3/8"	PP6VFC6-MG	17.35	10

Valve Elbow Unions



tube to tube

Tube OD 1	Tube OD 2	Nylon Part #	Price/E	Pkg Qty
1/4"	1/4"	PP4VEU4-MG	\$21.10	10
1/4"	3/8"	PP4VEU6-MG	20.35	10
3/8"	1/4"	PP6VEU4-MG	19.60	10
3/8"	3/8"	PP6VEU6-MG	18.65	10

TrueSeal™ Check Valves

Application:

Push-to connect check valves ensure protection against reversal of flow. The valves have an arrow molded into the body to indicate the direction of flow. Valves are designed for connection with either thermoplastic or soft metal tubing and are intended for use with liquids only.

Features:

- body material: acetal
- O-ring: EPDM
- metal grip edge: 300 stainless steel
- NSF-51 listed
- maximum operating pressure: **150 PSI** (dependent on tubing used)
- temperature range: **34°F to 150°F** (1°C to 65°C)
- cracking pressure: 1/3 PSI



tube to tube

Tube OD	Acetal Part #	Price/E	Pkg Qty
1/4"	A4VC4-MG	\$23.00	25
3/8"	A6VC6-MG	26.95	25