

Double Clapper Siamese Connections

**Features:**

- double drop clapper with (2) pin lug swivel inlets provides required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply (250 GPM minimum per inlet)
- exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes
- maximum operating pressure: **175 PSI** at 70°F (21°C)
- finish: -P polished or -C polished chrome plated
- U/L listed and FM approved


back outlet
21-132

Outlet Female NPT	(2) Inlets Female	Branding	Cast Brass Part #	Price	Wt. Lbs.
4"	2½" NST(NH)	AutoSprinkler	DCS4025F	\$855.70	16.0
		AutoSprinkler	DCS4025F-P	969.70	16.0
		AutoSprinkler	DCS4025F-C	1036.40	16.0
		StandPipe	DCS4025F-SP	855.70	16.0
		No Branding	DCS4025F-NB	855.70	16.0
	2½" CT		DCS4025 ¹	POR	16.0
4"	3" NST(NH)	AutoSprinkler	DCS4030F	878.80	18.5
	3" NST(NH)	AutoSprinkler	DCS4030NYFD	878.80	18.5
6"	2½" NYFD	AutoSprinkler	DCS6025F	962.45	22.0
	2½" NST(NH)	StandPipe	DCS6025F-SP	962.45	22.0
	2½" CT		DCS6025 ¹	POR	22.0

¹ Customer Thread (*must specify*) refer to legend on page 566

Dimensions

Size	A	B
4" x 2½" x 2½"	9⅝"	12¼"
6" x 2½" x 2½"	10¼"	11¾"
4" x 3" x 3"	10"	12½"
6" x 3" x 3"	10⅜"	12½"

bottom outlet
21-133

Outlet Female NPT	(2) Inlets Female	Branding	Cast Brass Part #	Price	Wt. Lbs.
4"	2½" NST(NH)	AutoSprinkler	90DCS4025F	\$847.10	16.0
		AutoSprinkler	90DCS4025F-P	968.35	16.0
		AutoSprinkler	90DCS4025F-C	998.65	16.0
		StandPipe	90DCS4025F-SP	847.10	16.0
		No Branding	90DCS4025F-NB	847.10	16.0
	2½" CT		90DCS4025 ¹	POR	16.0
4"	3" NST(NH)	AutoSprinkler	90DCS4030F	940.00	19.5
	3" NYFD	AutoSprinkler	90DCS4030NYFD	940.00	19.5
		StandPipe	90DCS4030NYFDSP	940.00	19.5
6"	2½" NST(NH)	AutoSprinkler	90DCS6025F	867.25	17.5
		StandPipe	90DCS6025F-SP	867.25	17.5
	2½" CT		90DCS6025 ¹	POR	17.5
	3" NYFD	AutoSprinkler	90DCS6030NYFD	2072.30	17.5

¹ Customer Thread (*must specify*) refer to legend on page 566

Dimensions

Size	A	B	C
4" x 2½" x 2½"	11¾"	9⅝"	7¼"
6" x 2½" x 2½"	11¾"	10¼"	7¼"
4" x 3" x 3"	12½"	10⅝"	7½"
6" x 3" x 3"	12¼"	10⅝"	7¼"

- special threads, branding and finishes are available, consult Dixon for information
- replacement swivels can be ordered on page 566



polished

P

