

# Locking Devices

## Insul-Lock Plus Devices

### 20A Connector

# HUBBELL

### Features

- Insulgrip style body design
- Accepts up to #12/3 AWG SO cable
- UL Enclosure type 4X and IP65 rated
- Disconnectable under load
- Multiple strain relief collets to accommodate wide range of cables
- Industry standard mating



### Ordering Information

Description	UPC	Catalog Number
Locking male cable connector, power out, screw terminals	783585580869	HBLMC
Cord Size	Color	
Accepts #18/3 up to #12/3 AWG SO Cable	Black	

### Listings

cULus  
UL50E Encl. type 4X when mated to Insul-lock plus HBLFC  
or when mated to HBLFP or HBLFPD in combination with HBLFPC or HBLFPDC  
IP65 rated when mated to Insul-lock plus HBLFC  
or when mated to HBLFP or HBLFPD in combination with HBLFPC or HBLFPDC

### Specifications

Body	Thermoplastic
Contacts	Copper Alloy
Weight	0.1

### Performance

Electrical	
Amperage	20A
Voltage	up to 250V AC

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

