



Product Information Packet

AOM3708T

5 AIR OVERHP,1150RPM,3PH,60HZ,215T,3732M

Part Detail							
Revision:	C	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Elec. Spec:	37WGS070	CD Diagram:	CD0005	Mfg Plant:	
Mech. Spec:	37F359	Layout:	37LYF359	Poles:	06	Created Date:	11-30-2010
Base:	RG	Eff. Date:	08-05-2016	Leads:	9#14 36" LG	Y	

Specs			
Catalog Number:	AOM3708T	Heater Indicator:	No Heater
Enclosure:	TEAO	Insulation Class:	F
Frame:	215T	Inverter Code:	Not Inverter
Frame Material:	Steel	KVA Code:	J
Output @ Frequency:	5.000 HP @ 60 HZ	Lifting Lugs:	Standard Lifting Lugs
Synchronous Speed @ Frequency:	1200 RPM @ 60 HZ	Locked Bearing Indicator:	Locked Bearing
Voltage @ Frequency:	208.0 V @ 60 HZ	Motor Lead Quantity/Wire Size:	9 @ 14 AWG
	230.0 V @ 60 HZ	Motor Lead Exit:	Ko Box
	460.0 V @ 60 HZ	Motor Lead Termination:	Flying Leads
XP Class and Group:	None	Motor Type:	3732M
XP Division:	Not Applicable	Mounting Arrangement:	F1
Agency Approvals:	UR	Power Factor:	71
	CSA	Product Family:	General Purpose
Auxillary Box:	No Auxillary Box	Pulley End Bearing Type:	Ball
Auxillary Box Lead Termination:	None	Pulley Face Code:	Standard
Base Indicator:	Rigid	Pulley Shaft Indicator:	Standard
Bearing Grease Type:	Polyrex EM (-20F +300F)	Rodent Screen:	None
Blower:	None	Shaft Extension Location:	Pulley End

Current @ Voltage:	15.200 A @ 230.0 V	Shaft Ground Indicator:	No Shaft Grounding
	16.500 A @ 208.0 V	Shaft Rotation:	Reversible
	7.600 A @ 460.0 V	Shaft Slinger Indicator:	No Slinger
Design Code:	B	Speed Code:	Single Speed
Drip Cover:	No Drip Cover	Motor Standards:	NEMA
Duty Rating:	CONT	Starting Method:	Direct on line
Electrically Isolated Bearing:	Not Electrically Isolated	Thermal Device - Bearing:	NONE (OLD)
Feedback Device:	NO FEEDBACK	Thermal Device - Winding:	None
Front Face Code:	Standard	Vibration Sensor Indicator:	No Vibration Sensor
Front Shaft Indicator:	None	Winding Thermal 1:	None
		Winding Thermal 2:	None

Nameplate NP1256L

CAT.NO.	AOM3708T										
SPEC.	37F359S070G1										
HP	5 AIR OVER										
VOLTS	208-230/460										
AMP	16.5-15.2/7.6										
RPM	1150										
FRAME	215T				HZ		60			PH	3
SER.F.	1.00		CODE		J	DES		B	CLASS		F
NEMA-NOM-EFF	86.5			PF		71					
RATING	40C AMB-CONT										
CC					USABLE AT 208V						
DE	6307				ODE		6206				
ENCL	TEAO		SN								
	1275 FPM AT 170CFM										

Parts List		
Part Number	Description	Quantity
SA213458	SA 37F359S070G1	1.000 EA
RA200679	RA 37F359S070G1	1.000 EA
HW3200A01	3/8-16X3/4 I-BLT WELDED F/S	1.000 EA
37CB3004	37 CB CASTING W/1.09 LEAD HOLE @ 6:00	1.000 EA
37GS1000SP	GASKET, CONDUIT BOX STD., .06 THICK LEXI	1.000 EA
10XN2520A10	1/4-20X 5/8 HEX HD X	2.000 EA
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
37EP3101A02	FR ENDPLATE, 37L&M-TENV MTR, MACH	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
HW5100A06	W2420-025 WVY WSHR (WB)	1.000 EA
37EP3100A09	PU ENDPLATE, MACH	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
10XN2520A28	1/4-20X 1 3/4 HEX HD	4.000 EA
HW1001A25	LOCKWASHER 1/4, ZINC PLT .493 OD, .255 I	4.000 EA
XY3118A12	5/16-18 HEX NUT DIRECTIONAL SERRATION	4.000 EA
37CB4516	LIPPED LID FOR 37 FRAME NEC KOBX	1.000 EA
37GS1008	37 GS FOR CB LID - LEXIDE	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 EA
HW2501F21	KEY, 5/16 SQ X 2.375	1.000 EA
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
LB1115N	LABEL,LIFTING DEVICE (ON ROLLS)	1.000 EA
MJ1000A02	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB

Parts List (continued)		
Part Number	Description	Quantity
MG1000G27	MED CHARCOAL METALLIC GREY 400-0096	0.028 GA
HA3104A14	THRUBOLT- 5/16-18 X12.125(OHIO)	4.000 EA
LC0005E01	CONN.DIA./WARNING LABEL (LC0005/LB1119N)	1.000 EA
NP1256L	ALUM UL CSA CC INDUSTRIAL MOTOR A60	1.000 EA
36PA1001	PKG GRP, PRINT PK1017A06	1.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (1200/bx) 5/18	1.000 EA

Accessories		
Part Number	Description	Multiplier
37-3301	C FACE KIT	P1

AC Induction Motor Performance Data

Record # 37121 - Typical performance - not guaranteed values

Winding: 37WGS070-R007	Type: 3732M	Enclosure: TEAO
-------------------------------	--------------------	------------------------

Nameplate Data				460 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	5 AIR OVER			Full Load Torque	22.6 LB-FT
Volts	208-230/460			Start Configuration	direct on line
Full Load Amps	16.5-15.2/7.6			Breakdown Torque	68.1 LB-FT
R.P.M.	1150			Pull-up Torque	43.6 LB-FT
Hz	60	Phase	3	Locked-rotor Torque	48.9 LB-FT
NEMA Design Code	B	KVA Code	J	Starting Current	47.8 A
Service Factor (S.F.)	1			No-load Current	4.09 A
NEMA Nom. Eff.	86.5	Power Factor	71	Line-line Res. @ 25°C	2.03 Ω
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	79°C
				Locked-rotor Power Factor	24
				Rotor inertia	0.796 LB-FT ²

Load Characteristics 460 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	33	53	64	71	74	76
Efficiency	79.7	86.7	87.3	86.7	84.6	82.2
Speed	1189	1178	1166	1153	1136	1117
Line amperes	4.33	5.15	6.24	7.6	9.36	11.3

Performance Graph at 460V, 60Hz, 5.0HP Typical performance - Not guaranteed values





