2

Locking Handle Brass Ball Valves

Application:

for control of air, water, oil and gas in hose or pipe lines

Features:

for other services, please contact Dixon

- pressure rating: 600 PSI WOG; 150 PSI saturated steam
- blow-out proof RPTFE stem
- chrome-plated brass ball
- Stainless steel sliding lock mechanism secures handle in open or closed position; can be padlocked opened or closed.
- plated steel handles and nuts with vinyl sleeves
- full and standard port valves are repairable

female NPT x female NPT

Size	Port	Brass	
		Part #	Price/E
1/4"	full	BBLV25	\$46.80
3/8"	full	BBLV38	46.80
1/2"	full	BBLV50	46.80
3/4"	standard	BBLV75	69.85
1"	standard	BBLV100	85.15
11⁄4"	standard	BBLV125	135.30
1½"	standard	BBLV150	169.80
2"	standard	BBLV200	209.90



Brass Ball Valves

Application:

for air service only

Features:

- pressure rating: 600 PSI
- brass valve
- chromium plated ball
- RTFE seats and stuffing box ring
- blow-out proof stem
- adjustable packing gland

female NPT x male NPT

Size	Port	Brass	
		Part #	Price/E
1/2"	full	BMV50	\$43.10
3/4"	standard	BMV75	68.60
1"	standard	BMV100	97.95



"Deadman" Spring Return Handle Bronze Ball Valves

Features:

- pressure rating: 600 PSI WOG; 150 PSI saturated steam
- vacuum service to 29 inches Hg
- stainless steel lever
- chromium plated ball
- RTFE seats and stuffing box ring
- blow-out proof stem design
- adjustable packing gland
- spring return closes valve when not held open
- operating torque approximately three times standard valve torque

female NPT x female NPT



