



TERMINAL LUGS			
AMPERES	MAX WIRE	MIN WIRE	TYPE
60	#2	#14	AL
100	1/0 AWG	#14	AL

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATING	AMPERE RATING	WIRING DIAG	240 VAC				480 VAC				600 VAC				125 VDC ①		250 VDC ①		600 VDC ①	
				2PH		3PH		2PH		3PH		2PH		3PH		STD	MAX	STD	MAX	STD	MAX
				STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX	STD	MAX
DTU462	600VAC:600VDC	60	A	NA	20	NA	20	NA	40	NA	50	NA	50	NA	60	NA	5	NA	10	NA	30
DTU463	600VAC:600VDC	100	A	NA	30	NA	40	NA	50	NA	75	NA	50	NA	75	NA	7.5	NA	20	NA	50

NOTES:
 UL LISTED - FILE E-2875
 FINISH - GRAY BAKED ENAMEL
SHORT CIRCUIT CURRENT RATING:
 10,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS H OR K FUSES.
 200,000 AMPERES WHEN USED IN CONJUNCTION WITH CLASS J OR R FUSES.
 ① FOR DC RATINGS USE 2 SWITCHING POLES.
 ② FIELD CONVERTIBLE TO FEED TWO ALTERNATE LOADS FROM A SINGLE SOURCE

HEAVY DUTY SAFETY SWITCHES
 VISIBLE BLADES
 60-100 AMPERE
 ENCLOSURE - TYPE 1
 NOT FUSIBLE



SQUARE D COMPANY

DWG# 3199
 NO.