



Product Information Packet

EM3615T-57

5HP,1450RPM,3PH,50HZ,184T,3646M,TEFC,F1

Part Detail							
Revision:	-	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Elec. Spec:	36WGR998	CD Diagram:	CD0022	Mfg Plant:	
Mech. Spec:	36A001	Layout:	36LYA001	Poles:	04	Created Date:	12-22-2015
Base:	RG	Eff. Date:	01-04-2016	Leads:	6#14		

Specs			
Catalog Number:	EM3615T-57	Insulation Class:	F
Enclosure:	TEFC	Inverter Code:	Inverter Ready
Frame:	184T	KVA Code:	K
Frame Material:	Steel	Lifting Lugs:	No Lifting Lugs
Output @ Frequency:	5.000 HP @ 50 HZ	Locked Bearing Indicator:	No Locked Bearing
Synchronous Speed @ Frequency:	1500 RPM @ 50 HZ	Motor Lead Quantity/Wire Size:	6 @ 14 AWG
Voltage @ Frequency:	400.0 V @ 50 HZ	Motor Lead Exit:	Ko Box
	230.0 V @ 50 HZ	Motor Lead Termination:	Flying Leads
XP Class and Group:	None	Motor Type:	3646M
XP Division:	Not Applicable	Mounting Arrangement:	F1
Agency Approvals:	UR	Power Factor:	75
	WEEE	Product Family:	General Purpose
	CSA	Pulley End Bearing Type:	Ball
	CE	Pulley Face Code:	Standard
Auxillary Box:	No Auxillary Box	Pulley Shaft Indicator:	Standard
Auxillary Box Lead Termination:	None	Rodent Screen:	None
Base Indicator:	Rigid	RoHS Status:	ROHS COMPLIANT
Bearing Grease Type:	Polyrex EM (-20F +300F)	Shaft Extension Location:	Pulley End

Blower:	None	Shaft Ground Indicator:	No Shaft Grounding
Current @ Voltage:	13.800 A @ 230.0 V	Shaft Rotation:	Reversible
	8.000 A @ 400.0 V	Shaft Slinger Indicator:	No Slinger
Design Code:	B	Speed Code:	Single Speed
Drip Cover:	No Drip Cover	Motor Standards:	NEMA
Duty Rating:	CONT	Starting Method:	Direct on line
Electrically Isolated Bearing:	Not Electrically Isolated	Thermal Device - Bearing:	NONE (OLD)
Feedback Device:	NO FEEDBACK	Thermal Device - Winding:	None
Front Face Code:	Standard	Vibration Sensor Indicator:	No Vibration Sensor
Front Shaft Indicator:	None	Winding Thermal 1:	None
Heater Indicator:	No Heater	Winding Thermal 2:	None

Nameplate NP2716L

CAT NO	EM3615T-57										
SPEC.	36A001R998G1										
HP	5							PH	3		
VOLTS	230/400										
AMP	13.8/8										
RPM	1450										
FRAME	184T				HZ	50		I.P.	54		
SER.F.	1.15		CODE	K		DES	B		CL	F	
NOM.EFF.	88.4				% (100%)						
PF	75				USABLE AT 208V						
RATING	40C AMB-CONT							CC			
DE BRG	6206				ODE	6205					
ENCL	TEFC		SN								
BLANK	IE3 - 90.1 (75%) 89.0 (50%)										

Parts List		
Part Number	Description	Quantity
SA312301	SA 36A001R998G1	1.000 EA
RA299743	RA 36A001R998G1	1.000 EA
36CB3004	36 CB CASTING W/1.09 DIA LEAD HOLE @ 6:0	1.000 EA
36GS1000SP	GASKET-CONDUIT BOX, .06 THICK #SV-330 LE	1.000 EA
51XB1016A08	10-16X 1/2HXWSSLD SERTYB	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
HW3001B01	BRASS CUP WASHER, FOR #10 SCREW	1.000 EA
36EP3104A01	FREP MACH ASSEMBLY FOR ROUTING	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 EA
36EP3100A01SP	PUEP ASSEMBLY FOR ROUTING PURPOSES	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
XY2520A12	1/4-20 HEX NUT, DIRECTIONAL SERRATIONS	4.000 EA
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	1.000 EA
36FH4009A102	IEC FH GREASER PRIMED	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
36CB4516	36 LIPPED CB LID - GALVANNEAL	1.000 EA
37GS1001SP	GASKET, CONDUIT BOX LID, .06 THICK LEXID	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 EA
HW2501E16	KEY, 1/4 SQ X 1.750	1.000 EA
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
HW3200A01	3/8-16X3/4 I-BLT WELDED F/S	1.000 EA
MJ1000A02	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB

Parts List (continued)		
Part Number	Description	Quantity
36FN3000C01SP	EXFN, PLASTIC, 5.25 OD, .912 ID	1.000 EA
MG1000G27	MED CHARCOAL METALLIC GREY 400-0096	0.022 GA
LB1115N	LABEL,LIFTING DEVICE (ON ROLLS)	1.000 EA
HA3101A28	THRUBOLT 1/4-20 X 12.500 OHIO ROD	4.000 EA
HA4067A01	PUSH IN DRAIN FITTING (BLACK)	1.000 EA
HA4067A01	PUSH IN DRAIN FITTING (BLACK)	1.000 EA
LB1119N	WARNING LABEL	1.000 EA
LC0034	CONNECTION LABEL	1.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (1200/bx) 5/18	1.000 EA
NP2716L	ALUM SUPER-E NEMA IE3 UL CSA CC CE	1.000 EA
G0PA1000	PKG GRP, PRINT PK1026A06	1.000 EA

AC Induction Motor Performance Data

Record # 54649 - Typical performance - not guaranteed values


Winding: 36WGR998-R002	Type: 3646M	Enclosure: OPEN
-------------------------------	--------------------	------------------------

Nameplate Data				380 V, 50 Hz: High Voltage Connection	
Rated Output (HP)	5			Full Load Torque	18.07 LB-FT
Volts	230/400			Start Configuration	direct on line
Full Load Amps	13.8/8			Breakdown Torque	67.85 LB-FT
R.P.M.	1450			Pull-up Torque	35.59 LB-FT
Hz	50	Phase	3	Locked-rotor Torque	43.26 LB-FT
NEMA Design Code	B	KVA Code	K	Starting Current	57.27 A
Service Factor (S.F.)	1.15			No-load Current	3.64 A
NEMA Nom. Eff.	88.4	Power Factor	75	Line-line Res. @ 25°C	1.91 Ω
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	82°C
S.F. Amps				Temp. Rise @ S.F. Load	102°C
				Locked-rotor Power Factor	44
				Rotor inertia	0.428 LB-FT ²


Load Characteristics 380 V, 50 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	41	64	76	82	85	86	79
Efficiency	84.3	89	89.5	88.5	87.1	85.1	88.1
Speed	1489	1476	1464	1449	1434	1416	1444
Line amperes	4.03	4.94	6.21	7.77	9.57	11.58	8.87

Performance Graph at 380V, 50Hz, 5.0HP Typical performance - Not guaranteed values



36LYA001



CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: ADD GREASER LEADERS (EA. END) TO LAYOUT OUT

REV. LTR: V

VERSION: 05

TDR: 000001001129

FILE: \AAA\00000\777

REVISED: 02:41:14 10/14/2016

BY: ENALEMO

MTL: -

BALDOR

STD HORZ 182-4T TEFC 36M

SH 1 of 1

36LYA001

