

	L D	1.25	32	
	E	1.50	38	
.25 DIA (6) .38 (10) .50 DIA (1.50 [13]			1	
.38 DIA [10] .78] 1.50	1.77 [45]			
[20] [38]	-1			

KNOCKOUTS

IN

.50

.75

1.00

1 25

SYMBOL

В

С

П

CONDUIT SIZE

ММ

13

19

25

32

DUAL DIMENSIONS: INCHES MILLIMETERS

	SYSTEM TYPE (IN)	SERVICE PROVIDED (OUT)	CATALOG NUMBER	METER SOCKET TYPE	NUMBER OF POSITIONS	TENANT CIRCUIT BREAKER (ORDER SEPARATELY)	LOAD NEUTRAL WIRE RANGE	EQUIPMENT GROUND WIRE RANGE
	3Ø 4W	1Ø 3W	EZMR313125 EZMR313125X EZMR313125CUX	5-JAW RINGLESS TYPE WITHOUT BYPASS	7	QO,QO-VH,OR QOH	(3) #14-2/0 AWG CU	(3) #14-2/0 AWG CU
208Y/120VAC	,	LZMIIIOIOIZO	5-JAW RINGLESS TYPE WITH HORN BYPASS	J	2-POLE	(3) #12-2/0 AWG AL	(3) #12-2/0 AWG AL	

EZ METER-PAK GANGABLE MULTI-METERING EQUIPMENT 125A MAX 3PH 4W METER SOCKET/CIRCUIT BREAKER 3-GANG BRANCH UNITS RAINPROOF NEMA TYPE 3R ENCLOSURES

by Schneider Electric DWG# 3404

APRIL 2012

GALVANNEALED STEEL.

FINISH - GRAY BAKED ENAMEL POWDER COAT PAINT OVER CLEANED

UL LISTED AS A MODULAR-PANELBOARD - FILE E131840, VOL. M SUITABLE FOR USE AS SERVICE EQUIPMENT. UNMETERED COMPARTMENTS ARE SEALABLE BY UTILITY.

SEE MARKINGS ON TENANT CIRCUIT BREAKER FOR WIRE RANGES.

(NOT SUITABLE FOR USE AS FLOOR STANDING EQUIPMENT).

GANGABLE MULTI-METERING EQUIPMENT IS DESIGNED FOR WALL MOUNTING ONLY