

Bearing		ISO dimensions						Weight	Locking nut	Locking device
Type	Version	d1 mm	d	d3	B1 kN	B2 kN	G	kg		
H 2356	OH	260	280	350	224	41	Tr 280x4	28,400	HM 56 T	MB 56
H 2356		260	280	350	224	41	Tr280x4	27,000	HM56T	MB56
H 3056		260	280	330	152	38	Tr280x4	17,700	HM3056	MS3056
H 3056	OH	260	280	330	152	38	Tr280x4	16,000	HM3056	MS3056
H 3156	OH	260	280	350	195	41	Tr280x4	25,100	HM56T	MB56
H 3156		260	280	330	195	41	Tr280x4	19,300	HM3056	MS3056
H 3956		260	280	330	121	38	Tr280x4	15,300	HM3056	MS3056
H 3060		280	300	360	168	42	Tr300x4	20,500	HM3060	MS3060
H 3060		280	300	360	168	42	Tr300x4	22,800	HM3060	MS3060
H 3060	OH	280	300	360	168	42	Tr300x4	20,500	HM3060	MS3060
H 3160	OH	280	300	380	208	40	Tr300x4	30,200	HM3160	MS3160
H 3160		280	300	380	208	40	Tr300x4	29,000	HM3160	MS3160
H 3260	OH	280	300	380	240	40	Tr300x4	34,100	HM3160	MS3160
H 3260		280	300	380	240	40	Tr300x4	32,000	HM3160	MS3160
H 3960		280	300	360	140	42	Tr300x4	20,000	HM3060	MS3060
H 3064	OH	300	320	380	171	42	Tr320x5	24,600	HM3064	MS3064
H 3064		300	320	380	171	42	Tr320x5	22,000	HM3064	MS3068-64
H 3164		300	320	400	226	42	Tr320x5	34,900	HM3164	MS3164
H 3164	OH	300	320	400	226	42	Tr320x5	32,000	HM3164	MS3164
H 3264	OH	300	320	400	258	42	Tr320x5	39,300	HM3164	MS3164
H 3264		300	320	400	258	42	Tr320x5	35,000	HM3164	MS3164
H 3964	OH	300	320	380	140	42	Tr320x5	21,500	HM3064	MS3064
H 3068		320	340	400	187	45	Tr340x5	28,700	HM3068	MS3068
H 3068		320	340	400	187	45	Tr340x5	27,000	HM3068	MS3068-64

