



SELECTION

IN-LINE HELICAL REDUCER (ILH)

SIZE: H_482

Service Factor 1.0 - Clamp Collar / 3 Pc Coupled / Separate

60 HZ

DOUBLE REDUCTION

NEMA MOTOR FRAME IEC MOTOR FRAME SEPARATE GROUP		56C 71D 71			--- 80D 80			140TC 90D 90			180TC 100D 100			--- 112D 112		
RATIO	OUTPUT RATING DATA	3450	1750	1160	3450	1750	1160	3450	1750	1160	3450	1750	1160	3450	1750	1160
4.28	Output RPM	-	-	-	806	409	271	806	409	271	806	409	271	806	409	271
	Input HP (Max) (C)	-	-	-	4.85	2.46	1.63	9.87	5.01	3.32	20.44	10.37	6.87	22.81	13.88	9.20
	Output Torque, In-Lb	-	-	-	379	379	379	772	772	772	1598	1598	1598	1784	2139	2139
	OHL Input Shaft	-	-	-	(A)	346	360	(A)	453	471	(A)	711	740	(A)	840	875
	OHL Output Shaft (B)	-	-	-	(A)	896	904	(A)	896	904	(A)	896	904	(A)	896	904
5.15	Output RPM	-	-	-	670	340	225	670	340	225	670	340	225	670	340	225
	Input HP (Max) (C)	-	-	-	4.84	2.46	1.63	9.85	5.00	3.31	20.41	10.35	6.86	21.22	12.88	8.54
	Output Torque, In-Lb	-	-	-	455	455	455	927	927	927	1920	1920	1920	1996	2390	2390
	OHL Input Shaft	-	-	-	(A)	346	360	(A)	454	473	(A)	708	737	(A)	840	875
	OHL Output Shaft (B)	-	-	-	(A)	904	919	(A)	904	919	(A)	904	919	(A)	904	919
6.06	Output RPM	-	-	-	569	289	191	569	289	191	569	289	191	569	289	191
	Input HP (Max) (C)	-	-	-	4.84	2.46	1.63	9.86	5.00	3.32	19.70	10.36	6.86	19.70	10.95	7.26
	Output Torque, In-Lb	-	-	-	536	536	536	1092	1092	1092	2181	2260	2181	2390	2390	
	OHL Input Shaft	-	-	-	(A)	346	360	(A)	452	471	(A)	709	739	(A)	843	877
	OHL Output Shaft (B)	-	-	-	(A)	904	919	(A)	904	919	(A)	904	919	(A)	904	919
6.79	Output RPM	-	-	-	508	258	171	508	258	171	508	258	171	508	258	171
	Input HP (Max) (C)	-	-	-	4.84	2.46	1.63	9.86	5.00	3.32	18.29	9.77	6.48	18.29	9.77	6.48
	Output Torque, In-Lb	-	-	-	601	601	601	1223	1223	1223	2269	2390	2390	2269	2390	2390
	OHL Input Shaft	-	-	-	(A)	346	360	(A)	456	474	(A)	709	739	(A)	844	878
	OHL Output Shaft (B)	-	-	-	(A)	904	919	(A)	904	919	(A)	904	919	(A)	904	919
6.90	Output RPM	-	-	-	500	254	168	500	254	168	500	254	168	500	254	168
	Input HP (Max) (C)	-	-	-	4.84	2.46	1.63	9.86	5.00	3.32	16.59	10.35	6.86	16.59	11.05	7.75
	Output Torque, In-Lb	-	-	-	611	611	611	1243	1243	1243	2091	2573	2573	2091	2747	2907
	OHL Input Shaft	-	-	-	(A)	346	360	(A)	453	471	(A)	711	740	(A)	844	878
	OHL Output Shaft (B)	-	-	-	(A)	904	919	(A)	904	919	(A)	904	919	(A)	904	919
8.29	Output RPM	-	-	-	416	211	140	416	211	140	416	211	140	416	211	140
	Input HP (Max) (C)	-	-	-	4.84	2.46	1.63	9.86	5.00	3.31	14.70	9.80	6.86	14.70	9.80	6.87
	Output Torque, In-Lb	-	-	-	734	734	734	1493	1493	1493	2226	2925	3091	2226	2925	3096
	OHL Input Shaft	-	-	-	(A)	343	360	(A)	454	473	(A)	710	737	(A)	837	878
	OHL Output Shaft (B)	-	-	-	(A)	919	937	(A)	919	937	(A)	919	937	(A)	919	937
9.76	Output RPM	-	-	-	353	179	119	353	179	119	353	179	119	353	179	119
	Input HP (Max) (C)	-	-	-	4.84	2.46	1.63	9.86	5.00	3.32	13.19	8.79	6.17	13.19	8.79	6.17
	Output Torque, In-Lb	-	-	-	864	864	864	1758	1758	1758	2352	3090	3270	2352	3090	3270
	OHL Input Shaft	-	-	-	(A)	346	360	(A)	452	471	(A)	711	739	(A)	839	871
	OHL Output Shaft (B)	-	-	-	904	919	937	904	919	937	904	919	937	904	919	937
10.93	Output RPM	316	160	106	316	160	106	316	160	106	316	160	106	316	160	106
	Input HP (Max) (C)	3.98	2.02	1.34	4.85	2.46	1.63	9.87	5.00	3.32	12.23	8.15	5.72	12.23	8.15	5.72
	Output Torque, In-Lb	795	795	795	968	968	968	1970	1970	1970	2442	3208	3396	2442	3208	3396
	OHL Input Shaft	(A)	209	218	(A)	346	360	(A)	456	474	(A)	712	740	(A)	840	872
	OHL Output Shaft (B)	904	919	937	904	919	937	904	919	937	904	919	937	904	919	937
12.25	Output RPM	282	143	95	282	143	95	282	143	95	282	143	95	282	143	95
	Input HP (Max) (C)	3.98	2.02	1.34	4.85	2.46	1.63	9.87	5.00	3.32	11.33	7.55	5.30	11.33	7.55	5.30
	Output Torque, In-Lb	891	891	891	1085	1085	1085	2208	2208	2208	2535	3331	3525	2535	3331	3525
	OHL Input Shaft	(A)	209	217	(A)	346	360	(A)	456	474	(A)	712	740	(A)	837	873
	OHL Output Shaft (B)	904	937	1142	904	937	1142	904	937	1142	904	937	1142	904	937	1142

(A) (B) (C) - See Footnotes page on inside back cover

Blank areas (-) indicate configuration not available

MOUNTING POSITIONS PAGE ILH-6	SELECTION OIL QUANTITIES PAGE ILH-6	SELECTION GEARMOTOR PAGE ILH-60	DIMENSIONS PAGE ILH-110
----------------------------------	--	------------------------------------	----------------------------



SELECTION

IN-LINE HELICAL REDUCER (ILH)

Service Factor 1.0 - Clamp Collar / 3 Pc Coupled / Separate

SIZE: H_482

60 HZ

DOUBLE REDUCTION

NEMA MOTOR FRAME IEC MOTOR FRAME SEPARATE GROUP		56C 71D 71			--- 80D 80			140TC 90D 90			180TC 100D 100			--- 112D 112		
RATIO	OUTPUT RATING DATA	3450	1750	1160	3450	1750	1160	3450	1750	1160	3450	1750	1160	3450	1750	1160
13.38	Output RPM	258	131	87	258	131	87	258	131	87	258	131	87	258	131	87
	Input HP (Max) (C)	3.98	2.02	1.34	4.84	2.46	1.63	9.86	5.00	3.32	10.67	7.11	4.99	10.67	7.11	4.99
	Output Torque, In-Lb	973	973	973	1184	1184	1184	2410	2410	2410	2609	3427	3627	2609	3427	3627
	OHL Input Shaft (A)	211	219	(A)	346	360	(A)	455	474	(A)	713	741	(A)	838	870	(A)
	OHL Output Shaft (B)	904	937	1142	904	937	1142	904	937	1142	904	937	1142	904	937	1142
14.68	Output RPM	235	119	79	235	119	79	235	119	79	235	119	79	235	119	79
	Input HP (Max) (C)	3.98	2.02	1.34	4.85	2.46	1.63	9.87	5.00	3.32	10.03	6.68	4.69	10.03	6.68	4.69
	Output Torque, In-Lb	1068	1068	1068	1300	1300	1300	2646	2646	2646	2689	3532	3738	2689	3532	3738
	OHL Input Shaft (A)	210	219	(A)	346	360	(A)	454	473	(A)	713	741	(A)	839	871	(A)
	OHL Output Shaft (B)	919	937	1142	919	937	1142	919	937	1142	919	937	1142	919	937	1142
16.17	Output RPM	213	108	72	213	108	72	213	108	72	213	108	72	213	108	72
	Input HP (Max) (C)	3.98	2.02	1.34	4.84	2.46	1.63	9.39	5.00	3.32	9.39	6.26	4.39	9.39	6.26	4.39
	Output Torque, In-Lb	1176	1176	1176	1431	1431	1431	2774	2913	2913	2774	3643	3856	2774	3643	3856
	OHL Input Shaft (A)	210	218	(A)	346	360	(A)	453	472	(A)	713	742	(A)	840	872	(A)
	OHL Output Shaft (B)	919	937	1142	919	937	1142	919	937	1142	919	937	1142	919	937	1142
17.55	Output RPM	197	100	66	197	100	66	197	100	66	197	100	66	197	100	66
	Input HP (Max) (C)	3.98	2.02	1.34	4.84	2.46	1.63	8.88	4.86	3.32	8.88	5.91	4.15	8.88	5.91	4.15
	Output Torque, In-Lb	1276	1276	1276	1553	1553	1553	2846	3071	3162	2846	3738	3957	2846	3738	3957
	OHL Input Shaft (A)	209	218	(A)	346	360	(A)	452	470	(A)	713	742	(A)	842	875	(A)
	OHL Output Shaft (B)	919	1142	1142	919	1142	1142	919	1142	1142	919	1142	1142	919	1142	1142
19.13	Output RPM	180	91	61	180	91	61	180	91	61	180	91	61	180	91	61
	Input HP (Max) (C)	3.87	2.02	1.34	4.84	2.46	1.63	8.37	4.65	3.22	8.37	5.58	3.83	8.37	5.58	3.83
	Output Torque, In-Lb	1353	1391	1391	1693	1693	1693	2924	3206	3343	2924	3842	3983	2924	3842	3983
	OHL Input Shaft (A)	210	218	(A)	346	359	(A)	452	472	(A)	714	742	(A)	841	874	(A)
	OHL Output Shaft (B)	919	1142	1517	919	1142	1517	919	1142	1517	919	1142	1517	919	1142	1517
20.95	Output RPM	165	84	55	165	84	55	165	84	55	165	84	55	165	84	55
	Input HP (Max) (C)	3.61	1.96	1.34	4.84	2.46	1.63	7.87	4.44	3.07	7.87	5.24	3.50	7.87	5.24	3.50
	Output Torque, In-Lb	1383	1482	1523	1854	1854	1854	3011	3352	3495	3011	3954	3983	3011	3954	3983
	OHL Input Shaft (A)	209	217	(A)	345	359	(A)	454	472	(A)	714	743	(A)	841	875	(A)
	OHL Output Shaft (B)	919	1142	1517	919	1142	1517	919	1142	1517	919	1142	1517	919	1142	1517
23.07	Output RPM	150	76	50	150	76	50	150	76	50	150	76	50	150	76	50
	Input HP (Max) (C)	3.35	1.82	1.25	4.85	2.46	1.63	7.37	4.23	2.92	7.37	4.79	3.18	-	-	-
	Output Torque, In-Lb	1413	1514	1569	2042	2042	2042	3104	3512	3661	3104	3983	3983	-	-	-
	OHL Input Shaft (A)	209	218	(A)	345	359	(A)	454	471	(A)	714	7y43	-	-	-	-
	OHL Output Shaft (B)	937	1142	1517	937	1142	1517	937	1142	1517	937	1142	1517	-	-	-
26.53	Output RPM	130	66	44	130	66	44	130	66	44	130	66	44	-	-	-
	Input HP (Max) (C)	3.00	1.63	1.12	4.85	2.46	1.63	6.69	3.92	2.71	6.69	4.17	2.76	-	-	-
	Output Torque, In-Lb	1453	1557	1614	2348	2348	2348	3241	3749	3910	3241	3983	3983	-	-	-
	OHL Input Shaft (A)	210	217	(A)	344	358	(A)	453	471	(A)	714	743	-	-	-	-
	OHL Output Shaft (B)	937	1142	1517	937	1142	1517	937	1142	1517	937	1142	1517	-	-	-
28.74	Output RPM	120	61	40	120	61	40	120	61	40	120	61	40	-	-	-
	Input HP (Max) (C)	2.81	1.53	1.05	4.85	2.46	1.63	6.33	3.77	2.55	6.33	3.85	2.55	-	-	-
	Output Torque, In-Lb	1475	1580	1638	2544	2544	2544	3324	3905	3983	3324	3983	3983	-	-	-
	OHL Input Shaft (A)	210	219	(A)	343	357	(A)	453	471	(A)	714	744	-	-	-	-
	OHL Output Shaft (B)	937	1517	1517	937	1517	1517	937	1517	1517	937	1517	1517	-	-	-

(A) (B) (C) - See Footnotes page on inside back cover
Blank areas (-) indicate configuration not available

MOUNTING POSITIONS PAGE ILH-6	SELECTION OIL QUANTITIES PAGE ILH-6	SELECTION GEARMOTOR PAGE ILH-60	DIMENSIONS PAGE ILH-110
----------------------------------	--	------------------------------------	----------------------------



SELECTION

IN-LINE HELICAL REDUCER (ILH)

SIZE: H_482

Service Factor 1.0 - Clamp Collar / 3 Pc Coupled / Separate

60 HZ

DOUBLE REDUCTION

NEMA MOTOR FRAME IEC MOTOR FRAME SEPARATE GROUP		56C 71D 71			--- 80D 80			140TC 90D 90			180TC 100D 100			--- 112D 112		
RATIO	OUTPUT RATING DATA	3450	1750	1160	3450	1750	1160	3450	1750	1160	3450	1750	1160	3450	1750	1160
31.77	Output RPM	109	55	37	109	55	37	109	55	37	109	55	37	-	-	-
	Input HP (Max) (C)	2.59	1.40	0.97	4.67	2.40	1.63	5.91	3.48	2.31	5.91	3.48	2.31	-	-	-
	Output Torque, In-Lb	1500	1607	1666	2712	2743	2812	3429	3983	3983	3429	3983	3983	-	-	-
	OHL Input Shaft (A)	210	218	(A)	343	356	(A)	453	472	(A)	715	744	(A)	-	-	-
37.06	OHL Output Shaft (B)	937	1517	1884	937	1517	1884	937	1517	1884	937	1517	1884	-	-	-
	Output RPM	93	47	31	93	47	31	93	47	31	-	-	-	-	-	-
	Input HP (Max) (C)	2.27	1.23	0.85	4.24	2.17	1.53	5.31	2.98	1.98	-	-	-	-	-	-
	Output Torque, In-Lb	1536	1646	1706	2868	2902	3076	3598	3983	3983	-	-	-	-	-	-
41.26	OHL Input Shaft (A)	210	217	(A)	343	360	(A)	455	473	-	-	-	-	-	-	-
	OHL Output Shaft (B)	1142	1517	1884	1142	1517	1884	1142	1517	1884	-	-	-	-	-	-
	Output RPM	84	42	28	84	42	28	84	42	28	-	-	-	-	-	-
	Input HP (Max) (C)	2.07	1.12	0.77	3.94	2.02	1.42	4.39	2.68	1.63	-	-	-	-	-	-
45.38	Output Torque, In-Lb	1558	1670	1731	2970	3005	3186	3312	3983	3659	-	-	-	-	-	-
	OHL Input Shaft (A)	210	211	(A)	343	360	(A)	455	473	-	-	-	-	-	-	-
	OHL Output Shaft (B)	1142	1884	1884	1142	1884	1884	1142	1884	1884	-	-	-	-	-	-
	Output RPM	76	39	26	76	39	26	76	39	26	-	-	-	-	-	-
51.28	Input HP (Max) (C)	1.90	1.03	0.71	3.19	1.91	1.19	3.19	2.44	1.19	-	-	-	-	-	-
	Output Torque, In-Lb	1577	1690	1752	2645	3120	2922	2645	3983	2922	-	-	-	-	-	-
	OHL Input Shaft (A)	211	211	(A)	343	360	(A)	456	474	-	-	-	-	-	-	-
	OHL Output Shaft (B)	1142	1884	1884	1142	1884	1884	1142	1884	1884	-	-	-	-	-	-
51.28	Output RPM	67	34	23	67	34	23	-	-	-	-	-	-	-	-	-
	Input HP (Max) (C)	1.71	0.93	0.64	2.08	1.87	0.77	-	-	-	-	-	-	-	-	-
	Output Torque, In-Lb	1599	1713	1776	1945	3454	2149	-	-	-	-	-	-	-	-	-
	OHL Input Shaft (A)	211	211	(A)	346	360	(A)	-	-	-	-	-	-	-	-	-
51.28	OHL Output Shaft (B)	1142	1884	1986	1142	1884	1884	-	-	-	-	-	-	-	-	-

NOTES:

(A) (B) (C) - See Footnotes page on inside back cover

Blank areas (-) indicate configuration not available

MOUNTING POSITIONS PAGE ILH-6	SELECTION OIL QUANTITIES PAGE ILH-6	SELECTION GEARMOTOR PAGE ILH-60	DIMENSIONS PAGE ILH-110
----------------------------------	--	------------------------------------	----------------------------



SELECTION

IN-LINE HELICAL REDUCER (ILH)

Service Factor 1.0 - Clamp Collar / 3 Pc Coupled / Separate

SIZE: H_483

60 HZ

TRIPLE REDUCTION

NEMA MOTOR FRAME IEC MOTOR FRAME SEPARATE GROUP		56C 71D 71			--- 80D 80			140TC 90D 90			180TC 100D 100		
RATIO	OUTPUT RATING DATA	3450	1750	1160	3450	1750	1160	3450	1750	1160	3450	1750	1160
35.59	Output RPM	97	49	33	97	49	33	97	49	33	97	49	33
	Input HP (Max) (C)	3.98	2.02	1.34	4.79	2.46	1.63	4.79	3.11	2.06	4.79	3.11	2.06
	Output Torque, In-Lb	2587	2587	2587	3114	3150	3150	3114	3983	3983	3114	3983	3983
	OHL Input Shaft (A)	209	209	218	(A)	346	360	(A)	457	475	(A)	715	744
	OHL Output Shaft (B)	1142	1517	1884	1142	1517	1884	1142	1517	1884	1142	1517	1884
41.38	Output RPM	83	42	28	83	42	28	83	42	28	83	42	28
	Input HP (Max) (C)	3.98	2.02	1.34	4.36	2.46	1.63	4.36	2.67	1.77	4.36	2.67	1.77
	Output Torque, In-Lb	3009	3009	3009	3295	3663	3663	3295	3983	3983	3295	3983	3983
	OHL Input Shaft (A)	211	211	219	(A)	346	360	(A)	457	475	(A)	708	737
	OHL Output Shaft (B)	1142	1517	1884	1142	1517	1884	1142	1517	1884	1142	1517	1884
45.91	Output RPM	75	38	25	75	38	25	75	38	25	75	38	25
	Input HP (Max) (C)	3.98	2.02	1.34	4.08	2.41	1.60	4.08	2.41	1.60	4.08	2.41	1.60
	Output Torque, In-Lb	3338	3338	3338	3418	3983	3983	3418	3983	3983	3418	3983	3983
	OHL Input Shaft (A)	210	210	219	(A)	346	360	(A)	457	476	(A)	709	738
	OHL Output Shaft (B)	1142	1884	1884	1142	1884	1884	1142	1884	1884	1142	1884	1884
50.00	Output RPM	69	35	23	69	35	23	69	35	23	-	-	-
	Input HP (Max) (C)	3.83	2.02	1.34	3.83	2.21	1.47	3.83	2.21	1.47	-	-	-
	Output Torque, In-Lb	3497	3635	3635	3497	3983	3983	3497	3983	3983	-	-	-
	OHL Input Shaft (A)	210	210	219	(A)	346	360	(A)	457	476	-	-	-
	OHL Output Shaft (B)	1142	1884	1986	1142	1884	1986	1142	1884	1986	-	-	-
55.92	Output RPM	62	31	21	62	31	21	62	31	21	-	-	-
	Input HP (Max) (C)	3.53	1.98	1.31	3.53	1.98	1.31	3.53	1.98	1.31	-	-	-
	Output Torque, In-Lb	3606	3983	3983	3606	3983	3983	3606	3983	3983	-	-	-
	OHL Input Shaft (A)	210	210	218	(A)	346	360	(A)	457	476	-	-	-
	OHL Output Shaft (B)	1517	1884	1986	1517	1884	1986	1517	1884	1986	-	-	-
61.14	Output RPM	56	29	19	56	29	19	56	29	19	-	-	-
	Input HP (Max) (C)	3.31	1.81	1.20	3.31	1.81	1.20	3.31	1.81	1.20	-	-	-
	Output Torque, In-Lb	3698	3983	3983	3698	3983	3983	3698	3983	3983	-	-	-
	OHL Input Shaft (A)	210	210	219	(A)	346	360	(A)	457	476	-	-	-
	OHL Output Shaft (B)	1517	1884	1986	1517	1884	1986	1517	1884	1986	-	-	-
67.10	Output RPM	51	26	17	51	26	17	51	26	17	-	-	-
	Input HP (Max) (C)	3.10	1.65	1.09	3.10	1.65	1.09	3.10	1.65	1.09	-	-	-
	Output Torque, In-Lb	3797	3983	3983	3797	3983	3983	3797	3983	3983	-	-	-
	OHL Input Shaft (A)	210	210	219	(A)	346	360	(A)	453	471	-	-	-
	OHL Output Shaft (B)	1517	1884	1986	1517	1884	1986	1517	1884	1986	-	-	-
73.99	Output RPM	47	24	16	47	24	16	47	24	16	-	-	-
	Input HP (Max) (C)	2.89	1.49	0.99	2.89	1.49	0.99	2.89	1.49	0.99	-	-	-
	Output Torque, In-Lb	3905	3983	3983	3905	3983	3983	3905	3983	3983	-	-	-
	OHL Input Shaft (A)	211	211	219	(A)	346	360	(A)	453	472	-	-	-
	OHL Output Shaft (B)	1517	1986	1986	1517	1986	1986	1517	1986	1986	-	-	-
82.02	Output RPM	42	21	14	42	21	14	42	21	14	-	-	-
	Input HP (Max) (C)	2.66	1.35	0.89	2.66	1.35	0.89	2.66	1.35	0.89	-	-	-
	Output Torque, In-Lb	3983	3983	3983	3983	3983	3983	3983	3983	3983	-	-	-
	OHL Input Shaft (A)	209	209	218	(A)	343	357	(A)	454	473	-	-	-
	OHL Output Shaft (B)	1517	1986	1986	1517	1986	1986	1517	1986	1986	-	-	-

(A) (B) (C) - See Footnotes page on inside back cover

Blank areas (-) indicate configuration not available

MOUNTING POSITIONS PAGE ILH-6	SELECTION OIL QUANTITIES PAGE ILH-6	SELECTION GEARMOTOR PAGE ILH-60	DIMENSIONS PAGE ILH-110
----------------------------------	--	------------------------------------	----------------------------



SELECTION

IN-LINE HELICAL REDUCER (ILH)

SIZE: H_483

Service Factor 1.0 - Clamp Collar / 3 Pc Coupled / Separate
TRIPLE REDUCTION

60 HZ

NEMA MOTOR FRAME IEC MOTOR FRAME SEPARATE GROUP		56C 71D 71			--- 80D 80			140TC 90D 90			180TC 100D 100		
RATIO	OUTPUT RATING DATA	3450	1750	1160	3450	1750	1160	3450	1750	1160	3450	1750	1160
92.91	Output RPM	37	19	12	37	19	12	37	19	12	-	-	-
	Input HP (Max) (C)	2.35	1.19	0.79	2.35	1.19	0.79	2.35	1.19	0.79	-	-	-
	Output Torque, In-Lb	3983	3983	3983	3983	3983	3983	3983	3983	3983	-	-	-
	OHL Input Shaft (A)	1884	209	218	(A)	344	358	(A)	455	473	-	-	-
	OHL Output Shaft (B)	1884	1986	1986	1884	1986	1986	1884	1986	1986	-	-	-
102.52	Output RPM	34	17	11	34	17	11	34	17	11	-	-	-
	Input HP (Max) (C)	2.13	1.08	0.72	2.13	1.08	0.72	2.13	1.08	0.72	-	-	-
	Output Torque, In-Lb	3983	3983	3983	3983	3983	3983	3983	3983	3983	-	-	-
	OHL Input Shaft (A)	1884	210	218	(A)	344	358	(A)	456	474	-	-	-
	OHL Output Shaft (B)	1884	1986	1986	1884	1986	1986	1884	1986	1986	-	-	-
115.91	Output RPM	30	15	10	30	15	10	30	15	10	-	-	-
	Input HP (Max) (C)	1.88	0.95	0.63	1.88	0.95	0.63	1.88	0.95	0.63	-	-	-
	Output Torque, In-Lb	3983	3983	3983	3983	3983	3983	3983	3983	3983	-	-	-
	OHL Input Shaft (A)	1884	210	219	(A)	345	359	(A)	456	474	-	-	-
	OHL Output Shaft (B)	1884	1986	1986	1884	1986	1986	1884	1986	1986	-	-	-
132.34	Output RPM	26	13	9	26	13	9	26	13	9	-	-	-
	Input HP (Max) (C)	1.65	0.84	0.55	1.65	0.84	0.55	1.65	0.84	0.55	-	-	-
	Output Torque, In-Lb	3983	3983	3983	3983	3983	3983	3983	3983	3983	-	-	-
	OHL Input Shaft (A)	1884	211	219	(A)	345	359	(A)	457	475	-	-	-
	OHL Output Shaft (B)	1884	1986	1986	1884	1986	1986	1884	1986	1986	-	-	-
150.48	Output RPM	23	12	8	23	12	8	-	-	-	-	-	-
	Input HP (Max) (C)	1.45	0.73	0.49	1.45	0.73	0.49	-	-	-	-	-	-
	Output Torque, In-Lb	3983	3983	3983	3983	3983	3983	-	-	-	-	-	-
	OHL Input Shaft (A)	1986	211	219	(A)	346	360	-	-	-	-	-	-
	OHL Output Shaft (B)	1986	1986	1986	1986	1986	1986	-	-	-	-	-	-
161.05	Output RPM	21	11	7	-	-	-	-	-	-	-	-	-
	Input HP (Max) (C)	1.35	0.69	0.46	-	-	-	-	-	-	-	-	-
	Output Torque, In-Lb	3983	3983	3983	-	-	-	-	-	-	-	-	-
	OHL Input Shaft (A)	1986	211	219	-	-	-	-	-	-	-	-	-
	OHL Output Shaft (B)	1986	1986	1986	-	-	-	-	-	-	-	-	-
185.66	Output RPM	19	9	6	-	-	-	-	-	-	-	-	-
	Input HP (Max) (C)	1.17	0.60	0.39	-	-	-	-	-	-	-	-	-
	Output Torque, In-Lb	3983	3983	3983	-	-	-	-	-	-	-	-	-
	OHL Input Shaft (A)	1986	211	220	-	-	-	-	-	-	-	-	-
	OHL Output Shaft (B)	1986	1986	1986	-	-	-	-	-	-	-	-	-
208.77	Output RPM	17	8	6	-	-	-	-	-	-	-	-	-
	Input HP (Max) (C)	1.04	0.53	0.35	-	-	-	-	-	-	-	-	-
	Output Torque, In-Lb	3983	3983	3983	-	-	-	-	-	-	-	-	-
	OHL Input Shaft (A)	1986	211	220	-	-	-	-	-	-	-	-	-
	OHL Output Shaft (B)	1986	1986	1986	-	-	-	-	-	-	-	-	-

NOTES:

(A) (B) (C) - See Footnotes page on inside back cover
Blank areas (-) indicate configuration not available

MOUNTING POSITIONS PAGE ILH-6	SELECTION OIL QUANTITIES PAGE ILH-6	SELECTION GEARMOTOR PAGE ILH-60	DIMENSIONS PAGE ILH-110
----------------------------------	--	------------------------------------	----------------------------