


30 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC
4 Pole, 5 Wire, Grounding



Dimensions in Inches (mm)

Plugs



30A 3ØY
120/208V AC
NEMA L21-30P
3 HP



30A 3ØY
240/415V AC
NEMA L26-30P



30A 3ØY
277/480V AC
NEMA L22-30P
10 HP



30A 3ØY
347/600V AC
NEMA L23-30P

Watertight Safety-Shroud®

IP66 SUITABILITY UL Type 4x, 12

Description	Cord Dia.	Catalog Number
Black Valox® housing, white Valox® clamps.	.350"-1.150" (9-29)	HBL2811SW HBL2801 HBL2821SW HBL2831SW

Safety-Shroud®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies.	.350"-1.150" (9-29)	HBL2811S - - -

Note: See page B-40 for accessories.

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Black and white nylon.	.350"-1.150" (9-29)	HBL2811 - HBL2821 HBL2831
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	HBL28CM11 - - -
Black and white for flat cable.	.350"-1.150" (9-29)	HBL2811FC - - -
All black nylon.	.350"-1.150" (9-29)	HBL2811BK - - -

Note: See page B-52 for accessories.

Flanged Inlets

Watertight Safety-Shroud®

IP66 SUITABILITY UL Type 4x, 12

Description	Catalog Number
Gray Valox® housing and flange.	HBL2815SW HBL2805 - -

Note: See page B-54 for accessories.

Insulgrip®

IP20 SUITABILITY

Description	Catalog Number
Nylon casing, back wired.	HBL2815 - HBL2825 HBL2835

Note: See page B-52 for accessories.

See pages B-69 and B-70 for technical information on Twist-Lock and Watertight Safety-Shroud devices.

Twist-Lock® 3-Phase Circuit Tester



Description	Rating	Catalog Number
3-Phase Circuit Tester	3Ø 120/208V AC Min. Voltage: 90V AC	HBL3PT2811 - - -

Note: Testers in other NEMA configurations can be developed upon request.
 See page B-53 for additional circuit testers.

HBLMITL - For use with Watertight Safety-Shroud receptacles, see page B-41.



Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.