



Valves



Single Hydrant Gate Valves with Handwheel

Application:

- protects fire hydrants from damage that can occur if they are used for throttling

Features:

- pin lug swivel, non-rising stem, red handwheel
- metal to metal seal
- UL listed
- for use on hydrants, standpipes, and fire pumps
- maximum operating pressure: **300 PSI** (water only) at **70°F (21°C)**

Inlet Female	Outlet Male	Forged Brass	
		Part #	Price/E
2½" NST (NH)	2½" NST (NH)	HGVW250F	\$540.75

Replacement Part



Description	Part #	Price/E
handwheel	HGVW250-W	\$50.15

Hydrant Gate Valves with Speed Handle

Features:

- protects fire hydrants from damage that can occur if they are used for throttling
- full 2½" waterway
- anodized throughout - minimum thickness 0.001"
- test pressure: **250 PSI**, working pressure: **100 PSI** at **70°F (21°C)**



Inlet Female Swivel	Outlet Male	Aluminum Alloy, 356-T6	
		Part #	Price/E
2½" NPSH	2½" NPSH	AHGV250	\$656.25
2½" NST (NH)	2½" NST (NH)	AHGV250F	656.25

Replacement Part



handwheel and knob

Description	Part #	Price/E
handwheel and knob	HGV-HDWHL	\$48.00
knob only	HGV-KNOB	22.80

Global Hydrant Gate Valves with Speed Handle

Application:

- protects fire hydrants from damage that can occur if they are used for throttling

Features:

- pin lug swivel, non-rising stem, aluminum speed handle
- non-metallic seal
- maximum operating pressure: **175 PSI** (water only) at **70°F (21°C)**



Inlet Female NST (NH)	Outlet Male NST (NH)	Aluminum Alloy	
		Part #	Price/E
2½"	2½"	AHGV250F-I	\$394.30

Replacement Part



Description	Aluminum	
	Part #	Price/E
speed handle	AHGV250F-H	\$68.75