

Dixon Worm Gear Clamps

Features:

- clamp meets SAEJ1508 which supercedes Mil Spec WW-C-440B
- four-piece construction
- screw design: 5/16" slotted hex head
- maximum recommended torque 50 in. lbs.
- **all clamps sold 10 per box**

Style HS material:

- band and housing: SAE 201/301 series stainless
- screw: SAE 1018 case-hardened, hex-free chrome zinc-plated steel

Style HSS material:

- band and housing: SAE 300 series stainless
- screw: SAE 300 series stainless

Band Width	Hose OD		style HS		Master Case Qty	style HSS		Master Case Qty
	from	to	Part #	Price /Each		Part #	Price /Each	
1/2"	7/16"	25/32"	HS6	\$1.50	200	HSS6	\$2.00	200
	1/2"	29/32"	HS8	1.50	200	HSS8	2.00	200
	9/16"	1-1/16"	HS10	1.50	500	HSS10	2.00	500
	11/16"	1-1/4"	HS12	1.55	500	HSS12	2.00	500
	13/16"	1-1/2"	HS16	1.55	500	HSS16	2.00	500
	13/16"	1-3/4"	HS20	1.55	500	HSS20	2.05	500
	1-1/16"	2"	HS24	1.55	500	HSS24	2.05	500
	1-5/16"	2-1/4"	HS28	1.60	500	HSS28	2.05	500
	1-9/16"	2-1/2"	HS32	1.60	500	HSS32	2.05	500
	1-13/16"	2-3/4"	HS36	1.65	500	HSS36	2.15	500
	2-1/16"	3"	HS40	2.00	200	HSS40	2.45	200
	2-5/16"	3-1/4"	HS44	2.20	200	HSS44	2.80	200
	2-9/16"	3-1/2"	HS48	2.20	200	HSS48	2.80	200
	2-13/16"	3-3/4"	HS52	2.40	200	HSS52	2.95	200
	3-1/16"	4"	HS56	2.40	200	HSS56	2.95	200
	3-5/16"	4-1/4"	HS60	2.50	200	HSS60	3.00	200
9/16"	3-9/16"	4-1/2"	HS64	2.50	200	HSS64	3.00	200
	1-7/8"	5"	HS72	2.70	100	HSS72	3.30	100
	2-1/2"	5-1/2"	HS80	3.10	100	HSS80	3.40	100
	3-1/8"	6"	HS88	3.20	100	HSS88	3.75	100
	3-5/8"	6-1/2"	HS96	3.25	100	HSS96	3.85	100
	4-1/8"	7"	HS104	3.30	100	HSS104	3.35	100
	5-5/8"	8-1/2"	HS128	4.90	100	HSS128	5.25	100
	7-1/8"	10"	HS152	5.25	100	HSS152	5.80	100
	9-3/8"	12-1/4"	HS188	5.75	100	HSS188	6.35	100
	10-1/8"	13"	HS200	5.80	100	HSS200	6.80	100
	10-7/8"	13-3/4"	HS212	5.90	100	HSS212	7.15	100
	11-5/8"	14-1/2"	HS224	6.55	100	HSS224	7.60	100
	12-3/8"	15-1/4"	HS236	7.10	100	HSS236	8.40	100
	13-1/8"	16"	HS248	7.45	100	HSS248	9.40	100
17-1/8"	20"	HS312	9.10	100	HSS312	10.75	100	



style HSS

K

Miniature Worm Gear Clamps

Features:

- meets SAE J1508
- screw design: 1/4" slotted hex head
- maximum recommended torque 15 in. lbs.
- **all clamps sold 10 per box**

Style MH material:

- band and housing: SAE 201/301 series stainless
- screw: SAE 1018 case-hardened, hex-free chrome zinc-plated steel

Style MAH material:

- band and housing: SAE 300 series stainless
- screw: SAE 300 series stainless

Band Width	Hose OD		style MH		Master Case Qty	style MAH		Master Case Qty
	from	to	Part #	Price /Each		Part #	Price /Each	
5/16"	7/32"	5/8"	MH4	\$1.15	500	MAH4	\$1.45	500
	7/16"	25/32"	MH6	1.15	500	MAH6	1.45	500
	1/2"	29/32"	MH8	1.35	200	MAH8	1.65	200
	9/16"	1-1/16"	MH10	1.35	200	MAH10	1.65	200
	11/16"	1-1/4"	MH12	1.40	200	MAH12	1.75	200
	15/16"	1-1/2"	MH16	1.40	200	MAH16	1.75	200
	1-3/16"	1-3/4"	MH20	1.45	200	MAH20	1.75	200



style MAH



Torque ratings correspond to the torque rating of the screw of the clamp and are not an indication of the working pressure of any hose assembly installed with this clamp.