

## Fire-Rated Poke-Throughs for Concrete Floors

### 2X2 Flush FRPT 3-Inch Core Hole Units



**ScrubShield**  
Complies with UL514A



#### 2X2 Flush FRPT – One-Piece Units

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Poke-Through	Black	<b>PT2X2BL</b>	2X2 Poke-Through	Black/Brass	<b>PT2X2BRS3</b>
	Gray	<b>PT2X2GY</b>		Brass Finish/Brass	<b>PT2X2BRS</b>
	Black	<b>PT2X2IGBL*</b>		Black/Brass	<b>PT2X2IGBRS3*</b>
	Gray	<b>PT2X2IGGY*</b>		Brass Finish/Brass	<b>PT2X2IGBRS*</b>


<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>■ <b>PT2X2FIT</b> through-floor fitting.</li> <li>■ Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks.</li> <li>■ Non-metallic cover.</li> <li>■ Painted aluminum flange.</li> <li>■ UL Listed and CSA Certified.</li> <li>■ Approved for use in the City of Chicago.</li> </ul>	 <b>PT2X2GY</b>	<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>■ <b>PT2X2FIT</b> through-floor fitting.</li> <li>■ Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks.</li> <li>■ Non-metallic cover.</li> <li>■ Solid brass flange.</li> <li>■ UL Listed and CSA Certified.</li> <li>■ Approved for use in the City of Chicago.</li> </ul>	 <b>PT2X2BRS3</b>
---	---	--	---

Note: \* Includes pre-wired 20A isolated ground duplex Style Line® receptacle.

#### 2X2 Flush FRPT – Two-Piece Units

Description	Catalog Number
Multi-Channel Through-Floor Fitting with (1) ¼ in. E.M.T. stem with junction box for power and (2) ½ in. E.M.T. stems for low voltage.	<b>PT2X2FIT</b>



  

<p>Specifications:</p> <ul style="list-style-type: none"> <li>■ UL Listed and CSA Certified.</li> <li>■ 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping (D900 Series Design)).</li> <li>■ For 2¼ in. to 7 in. floor thickness.</li> <li>■ UL installation spacing. Minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area.</li> <li>■ Approved for use in the City of Chicago.</li> </ul>	 <b>PT2X2FIT</b>
---	---

#### Service Fittings

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
2X2 Service Fitting	Black	<b>PT2X2SFBL</b>	2X2 Service Fitting	Black/Brass	<b>PT2X2SFBR3</b>
	Gray	<b>PT2X2SFGY</b>		Brass Finish/Brass	<b>PT2X2SFBR</b>

<ul style="list-style-type: none"> <li>■ Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks.</li> <li>■ Non-metallic cover.</li> <li>■ Painted aluminum flange.</li> <li>■ UL Listed and CSA Certified.</li> </ul>	 <b>PT2X2SFBL</b>	<ul style="list-style-type: none"> <li>■ Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks.</li> <li>■ Non-metallic cover.</li> <li>■ Solid brass flange.</li> <li>■ UL Listed and CSA Certified.</li> </ul>	 <b>PT2X2SFBR3</b>
--	---	---	--

#### Accessories

Description	Color/Material	Catalog Number
Non-Metallic Replacement Covers	Brass Finish	<b>PT2X2CBRS</b>
	Black	<b>PT2X2CBL</b>
	Gray	<b>PT2X2CGY</b>

 <b>PT2X2CBL</b>
--

Note: See page M-13 for 3-inch closure plug.  
See page M-20 for technical information.