
Series 1 Carded Miniature FRL's

Dixon offers the Series I line of miniature filters, filter/regulators, regulators and lubricators in prepackaged clear plastic units suitable for hanging on store peg racks or displays. The primary features of each unit are printed on the packaging. Each package contains 1 unit and an instruction sheet.



Features:

- 5 micron element
- 1 oz. reservoir
- inlet pressure **150 PSI** maximum at ambient temperature (70°F)

Carded Miniature Filter with Transparent Bowl


Port	Flow (SCFM)	Automatic Drain		Manual Drain	
Size		Part #	Price/E	Part #	Price/E
1/4"	24	F07-200AC	\$71.05	F07-200MC	\$60.55



Features:

- pressure range 5-100 PSI
- relieving type
- inlet pressure 250 PSI maximum at ambient temperature (70°F)
- supplied with a GC620 gauge





2.67

8.26 (210) **

164)

6.44

Carded Miniature Regulator

Port	SCFM	with Gauge	_
Size		Part #	Price/E
1/4"	15	R07-200RGC	\$69.10


Features:

- pressure range 5-100 PSI
- relieving type
- 5 micron element
- 1 oz. reservoir
- push to lock adjusting knob
- inlet pressure 150 PSI maximum at ambient temperature (70°F)
- supplied with a GC620 gauge
- bowl guard not available

Carded Miniature Filter/Regulator with Transparent Bowl

P	ort	Flow	Automatic	Drain	Manual D	rain
		(SCFM)	Part #	Price/E	Part #	Price/E
1	1/4"	14	B07-202AGC	\$134.20	B07-202MGC	\$122.10





1.63 (41) to remove bow

Features:

- 1 oz. reservoir
- inlet pressure 150 PSI maximum at ambient temperature (70°F)

Carded Miniature Lubricator

Port	Flow	Transparent Bowl	
Size	(SCFM)	Part #	Price/E
1/4"	14	L07-200AC	\$86.20





FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 100 PSIG inlet pressure for regulators, 90 PSIG all others.