


| | LINE A | LINE B | JOIN | JOIN |
|---|---|---|---|---|
| HIGH STD | 1 | 4 | 2,3,8 | J,5 |
| HIGH OPP | 1 | 4 | 2,3,5 | J,8 |
| LOW STD | 1,3,8 | 4 | – | 2,J,5 |
| LOW OPP | 1,3,5 | 4 | – | 2,J,8 |

NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

| | | | |
|---|---|---|---|
| REV. DESC: REMOVE 2–TERMINAL THERMAL DETAIL, SEE CD0008A02 | | | BALDOR ELECTRIC Co. |
| REV. LTR: F | VERSION: 01 | TDR: 000000360649 | |
| CD0008 | FILE: \AAA\00007\408 | REVISED: 10:56:54 04/18/2005 | TYPE L, DV, REV, THERMAL, 7 LEADS |
| | MTL: – | BY: ENJOEPO | |

CD0008