

Joint Sealant Gasket Material



Features:

- GORE-TEX® interchangeable
- Form-In-Place expanded PTFE gasket material with adhesive backing
- manufactured from 100% virgin PTFE
- unaffected by all common chemicals (pH from 0-14)
- unlimited shelf life
- resilient with low cold flow
- requires less force than standard gasket materials
- pressure range: vacuum to 3000 PSI
- temperature range: **-450°F to 600°F**
- made in the USA
- FDA compliant #21CFR177.1550
- larger spools are available, consult factory for price and availability

Size	Length	Part #	Price/E
1/4"	20'	LCJS4-20	\$69.45
1/4"	50'	LCJS4-50	159.55
3/8"	25'	LCJS6-25	127.50
1/2"	15'	LCJS8-15	127.50
3/4"	15'	LCJS12-15	291.85

Leak Detector



Features:

- detects leaks by forming bubbles which remain for up to ten minutes
- will not cause corrosion or deterioration
- color: fluorescent yellow
- non-toxic, non-freezing
- temperature range: **-7°F (-20°C) to 180°F (82°C)**
- meets Federal specification MIL-L-25567-C

Size	Part #	Price/E	Case Qty
8 oz.	LCLD	\$11.90	24

Dixon Coupling Lubricant



DCL80

Application:

For use in assembly operations involving natural or synthetic rubber or plastic. Also an excellent lubricant when rubber or plastic needs to be cut, machined, pressed, turned, trimmed or ground.

Feature:


- biodegradable lubricant for coupling shanks

Size	Part #	Price/E
1 liter	DCL20	\$36.50
4 liters	DCL80	94.50

WD-40 Smart Straw



Features:

- permanently attached straw
- flip up for a precision spray; flip down for regular spray action
- sold in case quantities only
- should not be used as a lubricant for coupling shanks 

Size	Part #	Price/E	Case Qty
11 oz.	WD40	\$21.00	12