


Wilkerson Heavy Duty Modular Coalescing Filters



- for removal of extremely fine oil mists, oil aerosols and microscopic particles
- A standard airline filter should be installed as a pre-filter when using a coalescing filter.
- 1.0 micron type B1 and 0.003 micron type D elements are optional
- differential pressure indicator changes from green to red with pressure loss



with metal bowl




Features:

- 0.01 micron type C element
- 1 qt. bowl
- differential pressure indicator eliminates the guesswork of element placement
- maximum operating conditions:
150 PSIG (10.3 bar) and **32°F to 150°F** (0°C to 65.5°C)

Size	Flow (SCFM)	With Metal Bowl	
		Automatic Drain	
		Part #	Price/E
1 1/4"	741	M32-0AAMB	\$1723.75



with metal bowl



Features:

- 0.01 micron type C element
- 1 qt. bowl
- differential pressure indicator eliminates the guesswork of element placement
- maximum operating conditions:
150 PSIG (10.3 bar) and **32°F to 150°F** (0°C to 65.5°C)

Size	Flow (SCFM)	With Metal Bowl	
		Automatic Drain	
		Part #	Price/E
1 1/2"	710	M35-0BAMB	\$1836.50
2"	710	M35-0CAMB	1836.50

See pages 226-229 for filter accessories.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure.