

Mini In-Line Lubricators

Features:

- can be refilled under line pressure
- oil capacity: ¼ fluid ounce
- flow rating: 22 SCFM at 100 PSIG
- maximum operating pressure: **200 PSIG**
- maximum temperature: **175°F**



Female NPT Inlet	Outlet	Aluminum	
		Part #	Price/E
¼"	¼" female NPT	ML200	\$75.25
¼"	¼" male NPT	ML200M	75.25
⅜"	⅜" male NPT	ML300M	75.25

F

Mini In-Line Filter

Features:

- either port may be used as an inlet port
- filter element rated at 5 microns
- flow rating: 17 SCFM inlet pressure at 100 PSIG
- maximum operating pressure: **200 PSIG**
- maximum temperature: **175°F**



Female NPT	Male NPT	Aluminum	
		Part #	Price/E
¼"	¼"	MF200	\$44.90
Description		Part #	Price/E
replacement element		FRP-95-199	\$14.00

In-Line Air Filter

Application:

- protects small air tools such as impact wrenches, nut runners, grinders and screwdrivers

Features:

- standard element is 40 micron ensuring minimum pressure drop
- elements can be replaced quickly
- male x female configuration
- compact housing
- maximum operating pressure: **500 PSI**
- temperature range: **35°F to 200°F**
- air flow: 140 SCFM
- filter can be used directly before the air tool



NPT	Overall Length	Diameter	Weight Lbs.	Anodized Aluminum	
				Part #	Price/E
¾"	3-13/16"	1-½"	.46	9076M	\$75.00

Miniature Non-Repairable General Purpose Regulators

Features:

- relieving piston allows reduction of downstream pressure when system is dead-ended
- reliable pressure regulation at air flows up to 13 SCFM
- left to right flow
- 5 to 125 PSIG outlet pressure adjustment range
- compact design and light weight construction
- wrench flats for easy installation
- supplied with a GC620 gauge



with gauge			without gauge		
Size	Part #	Price/E	Size	Part #	Price/E
¼"	R46-200RG	\$63.85	¼"	R46-200R	\$47.15