

Table No. 1

Specifications

Sprocket Number	Bush- ing	Bore Range		Type	No. Teeth	Diameters			Dimensions						Wt. Lbs
		Min.	Max.			P. D.	O. D.	Flange	E	F	H	K	L	M	
FOR 14M20 BELTS — 14mm PITCH — 20mm (.79") WIDE															
B14MCS-28-20	2012	1/2"	2	A1F	28	4.912"	4.802"	5.562"	—	1.36"		3.61	1.25"	.11"	3.9
B14MCS-29-20	2012	1/2	2	A1F	29	5.088	4.978	5.562	—	1.36		3.99	1.25	.11	4.5
B14MCS-30-20	2012	1/2	2	A1F	30	5.263	5.153	5.763	—	1.36		3.99	1.25	.11	4.8
B14MCS-31-20	2012	1/2	2	A1F	31	5.439	5.329	6.124	—	1.36		4.22	1.25	.11	5.5
B14MCS-32-20	2012	1/2	2	A1F	32	5.614	5.504	6.124	—	1.36		4.22	1.25	.11	5.8
B14MCS-33-20	2012	1/2	2	A1F	33	5.790	5.680	6.465	—	1.36		4.53	1.25	.11	6.3
B14MCS-34-20	2012	1/2	2	A1F	34	5.965	5.855	6.465	—	1.36		4.53	1.25	.11	6.8
B14MCS-35-20	2012	1/2	2	A1F	35	6.141	6.031	6.816	—	1.36		4.95	1.25	.11	7.3
B14MCS-36-20	2517	1/2	2 1/2	B1F	36	6.316	6.206	6.816	—	1.36	4.25	—	1.75	.39	7.6
B14MCS-37-20	2517	1/2	2 1/2	B1F	37	6.492	6.382	7.167	—	1.36	4.25	—	1.75	.39	8.2
B14MCS-38-20	2517	1/2	2 1/2	B1F	38	6.667	6.557	7.167	—	1.36	4.25	—	1.75	.39	8.8
B14MCS-39-20	2517	1/2	2 1/2	B1F	39	6.842	6.732	7.518	—	1.36	4.25	—	1.75	.39	9.8
B14MCS-40-20	2517	1/2	2 1/2	B1F	40	7.018	6.908	7.518	—	1.36	4.25	—	1.75	.39	10.1
B14MCS-43-20	2517	1/2	2 1/2	B1F	43	7.544	7.434	8.395	—	1.36	4.25	—	1.75	.39	11.7
B14MCS-45-20	3020	15/16	3	B1F	45	7.895	7.785	8.395	—	1.36	5.41	—	2	.64	13.5
B14MCS-48-20	3020	15/16	3	B1F	48	8.421	8.311	8.941	—	1.36	5.75	—	2	.64	16.5
B14MCS-50-20	3020	15/16	3	B1F	50	8.772	8.662	9.292	—	1.36	5.75	—	2	.64	18.3
B14MCS-53-20	3020	15/16	3	B1F	53	9.299	9.189	9.687	—	1.36	5.75	—	2	.64	20.5
B14MCS-56-20	3525	1 3/16	3 15/16	B1F	56	9.825	9.715	10.355	—	1.36	8.7	—	2.5	1.14	23.2
B14MCS-60-20	3525	1 3/16	3 15/16	B1F	60	10.527	10.417	11.067	—	1.36	8.75	—	2.5	1.14	27.5
B14MCS-63-20	3525	1 3/16	3 15/16	B1F	63	11.053	10.943	11.75	—	1.36	8.75	—	2.5	1.14	30.2
B14MCS-67-20	3525	1 3/16	3 15/16	B1F	67	11.755	11.645	12.5	—	1.36	8.75	—	2.5	1.14	31.3
B14MCS-71-20	3525	1 3/16	3 15/16	C1F	71	12.457	12.347	13.187	—	1.36	8.75	11.05	2.5	1.14	32.6
B14MCS-75-20	3525	1 3/16	3 15/16	C1F	75	13.158	13.048	13.73	—	1.36	8.75	11.68	2.5	1.14	35.5
B14MCS-80-20	3525	1 3/16	3 15/16	C2F	80	14.036	13.926	14.625	—	1.36	8.75	12.56	2.5	1.14	41.3
B14MCS-90-20	3525	1 3/16	3 15/16	C2	90	15.790	15.680	—	—	1.36	8.75	14.26	2.5	1.14	60
B14MCS-112-20	3525	1 3/16	3 15/16	C3	112	19.650	19.540	—	—	1.36	8.75	16.47	2.5	1.14	60
B14MCS-126-20	3525	1 3/16	3 15/16	C3	126	22.106	21.996	—	—	1.75	8.75	18.6	2.5	.75	70
B14MCS-140-20	3525	1 3/16	3 15/16	C3	140	24.562	24.452	—	—	1.75	8.75	21.04	2.5	.75	80
B14MCS-154-20	3525	1 3/16	3 15/16	C3	154	27.019	26.909	—	—	1.75	8.75	23.5	2.5	.75	82
B14MCS-168-20	3525	1 3/16	3 15/16	C3	168	29.475	29.365	—	—	1.75	8.75	25.9	2.5	.75	100
B14MCS-180-20	3525	1 3/16	3 15/16	C3	180	31.580	31.470	—	—	1.75	8.75	27.99	2.5	.75	135
B14MCS-200-20	3525	1 3/16	3 15/16	C3	200	35.089	34.979	—	—	1.75	8.75	31.46	2.5	.75	156
B14MCS-224-20	4030	1 7/16	4 7/16	C3	224	39.300	39.190	—	—	1.75	10	35.63	3	1.25	151
FOR 14M37 BELTS — 14mm PITCH — 37mm (1.46") WIDE															
PB14MCS-28-37	—	1	2 15/16	6F	28	4.912	4.802	5.562	.8	2.06	3.97	—	2.86	—	11.7
B14MCS-28-37	2012	1/2	2	A1F	28	4.912	4.802	5.562	—	2.06	—	3.61	1.25	.81	5.2
B14MCS-29-37	2517	1/2	2 1/2	A1F	29	5.088	4.978	5.562	—	2.06	—	3.99	1.75	.31	5.1
B14MCS-30-37	2517	1/2	2 1/2	A1F	30	5.263	5.153	5.763	—	2.06	—	3.99	1.75	.31	5.8
B14MCS-31-37	2517	1/2	2 1/2	A1F	31	5.439	5.329	6.124	—	2.06	—	4.22	1.75	.31	6.4
B14MCS-32-37	2517	1/2	2 1/2	A1F	32	5.614	5.504	6.124	—	2.06	—	4.22	1.75	.31	7.2
B14MCS-33-37	2517	1/2	2 1/2	A1F	33	5.790	5.680	6.465	—	2.06	—	4.53	1.75	.31	7.8
B14MCS-34-37	2517	1/2	2 1/2	A1F	34	5.965	5.855	6.465	—	2.06	—	4.53	1.75	.31	8.7
B14MCS-35-37	2517	1/2	2 1/2	A1F	35	6.141	6.031	6.816	—	2.06	—	4.95	1.75	.31	9.3
B14MCS-36-37	2517	1/2	2 1/2	A1F	36	6.316	6.206	6.816	—	2.06	—	4.95	1.75	.31	10.2
B14MCS-37-37	2517	1/2	2 1/2	A1F	37	6.492	6.382	7.167	—	2.06	—	5.27	1.75	.31	10.8
B14MCS-38-37	3020	15/16	3	A1F	38	6.667	6.557	7.167	—	2.06	—	5.27	2	.06	10.3
B14MCS-39-37	3020	15/16	3	A1F	39	6.842	6.732	7.518	—	2.06	—	5.54	2	.06	11.3
B14MCS-40-37	3020	15/16	3	A1F	40	7.018	6.908	7.518	—	2.06	—	5.54	2	.06	12.3
B14MCS-43-37	3020	15/16	3	A1F	43	7.544	7.434	8.395	—	2.06	—	6.16	2	.06	15.6
B14MCS-45-37	3020	15/16	3	A1F	45	7.895	7.785	8.395	—	2.06	—	6.42	2	.06	18
B14MCS-48-37	3020	15/16	3	A1F	48	8.421	8.311	8.941	—	2.06	—	6.96	2	.06	21.5
B14MCS-50-37	3020	15/16	3	A1F	50	8.772	8.662	9.292	—	2.06	—	7.44	2	.06	24.1
B14MCS-53-37	3020	15/16	3	A1F	53	9.299	9.189	9.687	—	2.06	—	7.84	2	.06	28.3
B14MCS-56-37	3525	1 3/16	3 15/16	B1F	56	9.825	9.715	10.355	—	2.06	8.7	—	2.5	.44	33
B14MCS-60-37	3525	1 3/16	3 15/16	B1F	60	10.527	10.417	11.067	—	2.06	8.75	—	2.5	.44	40.6
B14MCS-63-37	3525	1 3/16	3 15/16	B1F	63	11.053	10.943	11.75	—	2.06	8.75	—	2.5	.44	46.7
B14MCS-67-37	3525	1 3/16	3 15/16	B1F	67	11.755	11.645	12.5	—	2.06	8.75	—	2.5	.44	55.6
B14MCS-71-37	3525	1 3/16	3 15/16	B1F	71	12.457	12.347	13.187	—	2.06	8.75	—	2.5	.44	61.2
B14MCS-75-37	3525	1 3/16	3 15/16	C1F	75	13.158	13.048	13.73	—	2.06	8.75	11.68	2.5	.44	46.9
B14MCS-80-37	3525	1 3/16	3 15/16	C2F	80	14.036	13.926	14.625	—	2.06	8.75	12.56	2.5	.44	52.5
B14MCS-90-37	3525	1 3/16	3 15/16	C2	90	15.790	15.68	—	—	2.06	8.75	14.26	2.5	.44	61.5
B14MCS-112-37	3525	1 3/16	3 15/16	C3	112	19.650	19.54	—	—	2.06	8.75	16.39	2.5	.44	89.1
B14MCS-126-37	3525	1 3/16	3 15/16	C3	126	22.106	21.996	—	—	2.06	8.75	18.6	2.5	.44	106
B14MCS-140-37	3525	1 3/16	3 15/16	C3	140	24.562	24.452	—	—	2.06	8.75	20.84	2.5	.44	125

NOTE — Numerals in Type Designations mean: 1 = Solid, 2 = Web, 3 = Arm Construction; F = Flanged Sprocket.

Table No. 1

Specifications

Sprocket Number	Bush- ing	Bore Range		Type	No. Teeth	Diameters			Dimensions							Wt. Lbs.
		Min.	Max.			P. D.	O. D.	Flange	E	F	H	K	L	M		
FOR 14M37 BELTS — 14mm PITCH — 37mm (1.46") WIDE - Continued																
B14MCS-154-37	4030	1 7/16	4 7/16	C3	154	27.019	26.909	—	—	2.06	10	23.5	3	.94	157	
B14MCS-168-37	4030	1 7/16	4 7/16	C3	168	29.475	29.365	—	—	2.06	10	25.51	3	.94	175	
B14MCS-180-37	4030	1 7/16	4 7/16	C3	180	31.580	31.470	—	—	2.06	10	27.59	3	.94	191	
B14MCS-200-37	4030	1 7/16	4 7/16	C3	200	35.089	34.979	—	—	2.06	10	31.07	3	.94	225	
B14MCS-224-37	4030	1 7/16	4 7/16	C3	224	39.300	39.190	—	—	2.06	10	35.24	3	.94	268	
FOR 14M68 BELTS — 14mm PITCH — 68mm (2.68") WIDE																
PB14MCS-28-68	—	1"	2 15/16"	6F	28	4.912"	4.802"	5.562"	.8"	3.33"	3.97	—	4.13"	—	17	
PB14MCS-29-68	—	1	3 3/16	6F	29	5.088	4.802	5.562	.8	3.33	4.35	—	4.13	—	19	
B14MCS-29-68	2517	1/2	2 1/2	A1F	29	5.088	4.978	5.562	—	3.33	—	3.99	1.75	1.58	7	
PB14MCS-30-68	—	1	3 3/16	6F	30	5.263	5.153	5.763	.8	3.33	4.35	—	4.13	—	20	
B14MCS-30-68	2517	1/2	2 1/2	A1F	30	5.263	5.153	5.763	—	3.33	—	3.99	1.75	1.58	8.2	
PB14MCS-31-68	—	1	3 7/16	6F	31	5.439	5.329	6.124	.8	3.33	4.57	—	4.13	—	22	
B14MCS-31-68	2517	1/2	2 1/2	A1F	31	5.439	5.329	6.124	—	3.33	—	4.22	1.75	1.58	8.8	
PB14MCS-32-68	—	1	3 7/16	6F	32	5.614	5.504	6.124	.8	3.33	4.57	—	4.13	—	23	
B14MCS-32-68	2517	1/2	2 1/2	A1F	32	5.614	5.504	6.124	—	3.33	—	4.22	1.75	1.58	10	
PB14MCS-33-68	—	1	3 1/2	6F	33	5.790	5.680	6.465	1	3.33	4.89	—	4.13	—	26	
B14MCS-33-68	2517	1/2	2 1/2	A1F	33	5.790	5.680	6.465	—	3.33	—	4.53	1.75	1.58	11	
PB14MCS-34-68	—	1	3 1/2	6F	34	5.965	5.855	6.465	1	3.33	4.89	—	4.13	—	27	
B14MCS-34-68	2517	1/2	2 1/2	A1F	34	5.965	5.855	6.465	—	3.33	—	4.53	1.75	1.58	12	
B14MCS-35-68	3020	15/16	3	A1F	35	6.141	6.031	6.816	—	3.33	—	4.95	2	1.33	10	
B14MCS-36-68	3020	15/16	3	A1F	36	6.316	6.206	6.816	—	3.33	—	4.95	2	1.33	12	
B14MCS-37-68	3020	15/16	3	A1F	37	6.492	6.382	7.167	—	3.33	—	5.27	2	1.33	12	
B14MCS-38-68	3020	15/16	3	A1F	38	6.667	6.557	7.167	—	3.33	—	5.27	2	1.33	14	
B14MCS-39-68	3020	15/16	3	A1F	39	6.842	6.732	7.518	—	3.33	—	5.54	2	1.33	15	
B14MCS-40-68	3020	15/16	3	A1F	40	7.018	6.908	7.518	—	3.33	—	5.54	2	1.33	16	
B14MCS-43-68	3020	15/16	3	A1F	43	7.544	7.434	8.395	—	3.33	—	6.16	2	1.33	18	
B14MCS-45-68	3020	15/16	3	A1F	45	7.895	7.785	8.395	—	3.33	—	6.42	2	1.33	22	
B14MCS-48-68	3525	1 3/16	3 15/16	A1F	48	8.421	8.311	8.941	—	3.33	—	6.96	2.5	.83	26	
B14MCS-50-68	3525	1 3/16	3 15/16	A1F	50	8.772	8.662	9.292	—	3.33	—	7.44	2.5	.83	28	
B14MCS-53-68	3525	1 3/16	3 15/16	A1F	53	9.299	9.189	9.687	—	3.33	—	7.84	2.5	.83	34	
B14MCS-56-68	3525	1 3/16	3 15/16	A1F	56	9.825	9.715	10.355	—	3.33	—	8.35	2.5	.83	39	
B14MCS-60-68	3525	1 3/16	3 15/16	A1F	60	10.527	10.417	11.067	—	3.33	—	9.06	2.5	.83	46	
B14MCS-63-68	3525	1 3/16	3 15/16	A1F	63	11.053	10.943	11.75	—	3.33	—	9.59	2.5	.83	52	
B14MCS-67-68	3525	1 3/16	3 15/16	D1F	67	11.755	11.645	12.500	—	3.33	8.75	10.36	2.5	.83	56	
B14MCS-71-68	3525	1 3/16	3 15/16	D1F	71	12.457	12.347	13.187	—	3.33	8.75	11.05	2.5	.83	64	
B14MCS-75-68	3525	1 3/16	3 15/16	D1F	75	13.158	13.048	13.73	—	3.33	8.75	11.68	2.5	.83	57	
B14MCS-80-68	3525	1 3/16	3 15/16	D1F	80	14.036	13.926	14.625	—	3.33	8.75	12.56	2.5	.83	62	
B14MCS-90-68	4030	1 7/16	4 7/16	D2	90	15.790	15.680	—	—	3.33	10	14.26	3	.33	86	
B14MCS-112-68	4030	1 7/16	4 7/16	D3	112	19.650	19.540	—	—	3.33	10	16.35	3	.33	135	
B14MCS-140-68	4030	1 7/16	4 7/16	D3	140	24.562	24.452	—	—	3.33	10	20.78	3	.33	189	
B14MCS-168-68	4535	1 15/16	4 15/16	C3	168	29.475	29.365	—	—	3.33	10.5	25.23	3.5	.17	259	
B14MCS-180-68	4535	1 15/16	4 15/16	C3	180	31.580	31.470	—	—	3.33	10.5	27.16	3.5	.17	288	
B14MCS-200-68	4535	1 15/16	4 15/16	C3	200	35.089	34.979	—	—	3.33	10.5	30.65	3.5	.17	331	
B14MCS-224-68	5040	2 7/16	5	C3	224	39.300	39.190	—	—	3.33	11	34.82	4	.67	404	
FOR 14M90 BELTS — 14mm PITCH — 90mm (3.54") WIDE																
PB14MCS-28-90	—	1 1/2	2 15/16	6F	28	4.912	4.802	5.562	.94	4.2	3.97	—	5.14	—	20	
PB14MCS-29-90	—	1 1/2	3 3/16	6F	29	5.088	4.978	5.562	.8	4.2	4.35	—	5	—	22	
PB14MCS-30-90	—	1 1/2	3 3/16	6F	30	5.263	5.153	5.763	.8	4.2	4.35	—	5	—	24	
PB14MCS-31-90	—	1 1/2	3 7/16	6F	31	5.439	5.329	6.124	.8	4.2	4.57	—	5	—	25	
PB14MCS-32-90	—	1 1/2	3 7/16	6F	32	5.614	5.504	6.124	.8	4.2	4.57	—	5	—	27	
PB14MCS-33-90	—	1 1/2	3 1/2	6F	33	5.790	5.680	6.465	1	4.2	4.89	—	5.2	—	30	
PB14MCS-34-90	—	1 1/2	3 1/2	6F	34	5.965	5.855	6.465	1	4.2	4.89	—	5.2	—	32	
PB14MCS-35-90	—	1 1/2	3 13/16	6F	35	6.141	6.031	6.816	1	4.2	5.3	—	5.2	—	35	
B14MCS-35-90	3020	15/16	3	A1F	35	6.141	6.031	6.816	—	4.2	—	4.95	2	2.2	12	
PB14MCS-36-90	—	1 1/2	3 13/16	6F	36	6.316	6.206	6.816	1	4.2	5.3	—	5.2	—	36	
B14MCS-36-90	3020	15/16	3	A1F	36	6.316	6.206	6.816	—	4.2	—	4.95	2	2.2	14	
PB14MCS-37-90	—	1 1/2	4 1/8	6F	37	6.492	6.382	7.167	1	4.2	5.63	—	5.2	—	39	
B14MCS-37-90	3020	15/16	3	A1F	37	6.492	6.382	7.167	—	4.2	—	5.27	2	2.2	14	
PB14MCS-38-90	—	1 1/2	4 1/8	6F	38	6.667	6.557	7.167	1	4.2	5.63	—	5.2	—	41	
B14MCS-38-90	3020	15/16	3	A1F	38	6.667	6.557	7.167	—	4.2	—	5.27	2	2.2	16	
PB14MCS-39-90	—	1 1/2	4 3/8	6F	39	6.842	6.732	7.518	1	4.2	5.89	—	5.2	—	44	
B14MCS-39-90	3020	15/16	3	A1F	39	6.842	6.732	7.518	—	4.2	—	5.54	2	2.2	17	
PB14MCS-40-90	—	1 1/2	4 3/8	6F	40	7.018	6.908	7.518	1	4.2	5.89	—	5.2	—	46	
B14MCS-40-90	3020	15/16	3	A1F	40	7.018	6.908	7.518	—	4.2	—	5.542	2	2.2	19	
B14MCS-43-90	3525	1 3/16	3 15/16	A1F	43	7.544	7.434	8.395	—	4.2	—	6.16	2.5	1.7	21	
B14MCS-45-90	3525	1 3/16	3 15/16	A1F	45	7.895	7.785	8.395	—	4.2	—	6.42	2.5	1.7	24	
B14MCS-48-90	3525	1 3/16	3 15/16	A1F	48	8.421	8.311	8.941	—	4.2	—	6.96	2.5	1.7	29	
B14MCS-50-90	3525	1 3/16	3 15/16	A1F	50	8.772	8.662	9.292	—	4.2	—	7.44	2.5	1.7	31	
B14MCS-53-90	3525	1 3/16	3 15/16	A1F	53	9.299	9.189	9.687	—	4.2	—	7.83	2.5	1.7	37	

NOTE — Numerals in Type Designations mean: 1 = Solid, 2 = Web, 3 = Arm Construction; F = Flanged Sprocket.

FOR 14M90 BELTS — 14mm PITCH — 90mm (3.54") WIDE - Continued

B14MCS-56-90	4030	1 7/16	4 7/16	A1F	56	9.825	9.715	10.355	—	4.2	—	8.35	3	1.2	43
B14MCS-60-90	4030	1 7/16	4 7/16	A1F	60	10.527	10.417	11.067	—	4.2	—	9.06	3	1.2	52
B14MCS-63-90	4030	1 7/16	4 7/16	A1F	63	11.053	10.943	11.75	—	4.2	—	9.59	3	1.2	59
B14MCS-67-90	4030	1 7/16	4 7/16	A1F	67	11.755	11.645	12.500	—	4.2	—	9.881	3	1.2	71
B14MCS-71-90	4030	1 7/16	4 7/16	A1F	71	12.457	12.347	13.187	—	4.2	—	10.67	3	1.2	82
B14MCS-75-90	4030	1 7/16	4 7/16	A1F	75	13.158	13.048	13.73	—	4.2	—	11.63	3	1.2	96
B14MCS-80-90	4030	1 7/16	4 7/16	D1F	80	14.036	13.926	14.625	—	4.2	10	12.56	3	1.2	94
B14MCS-90-90	4030	1 7/16	4 7/16	D2	90	15.790	15.68	—	—	4.2	10	14.26	3	1.2	95
B14MCS-112-90	4535	1 15/16	4 15/16	D2	112	19.650	19.54	—	—	4.2	10.5	16.35	3.5	.7	173
B14MCS-140-90	5040	2 7/16	5	D3	140	24.562	24.452	—	—	4.2	11	20.74	4	.2	245
B14MCS-168-90	6050	4 7/16	5 15/16	C3	168	29.475	29.365	—	—	4.2	15.5	25.11	5	.8	395
B14MCS-180-90	6050	4 7/16	5 15/16	C3	180	31.580	31.470	—	—	4.2	15.5	27.06	5	.8	429
B14MCS-200-90	6050	4 7/16	5 15/16	C3	200	35.089	34.979	—	—	4.2	15.5	30.29	5	.8	493
B14MCS-224-90	6050	4 7/16	5 15/16	C3	224	39.300	39.190	—	—	4.2	15.5	34.46	5	.8	563

FOR 14M125 BELTS — 14mm PITCH — 125mm (4.92") WIDE

PB14MCS-28-125	—	1 1/2	2 15/16	6F	28	4.912	4.802	5.562	.89	5.61	3.97	—	6.5	—	25
PB14MCS-29-125	—	1 1/2	3 3/16	6F	29	5.088	4.978	5.562	.89	5.61	4.35	—	6.5	—	27
PB14MCS-30-125	—	1 1/2	3 3/16	6F	30	5.263	5.153	5.763	.89	5.61	4.35	—	6.5	—	29
PB14MCS-31-125	—	1 1/2	3 7/16	6F	31	5.439	5.329	6.124	.89	5.61	4.57	—	6.5	—	32
PB14MCS-32-125	—	1 1/2	3 7/16	6F	32	5.614	5.504	6.124	.89	5.61	4.57	—	6.5	—	34
PB14MCS-33-125	—	1 1/2	3 1/2	6F	33	5.790	5.680	6.465	1.08	5.61	4.89	—	6.69	—	37
PB14MCS-34-125	—	1 1/2	3 1/2	6F	34	5.965	5.855	6.465	1.08	5.61	4.89	—	6.69	—	40
PB14MCS-35-125	—	1 1/2	3 13/16	6F	35	6.141	6.031	6.816	1.08	5.61	5.3	—	6.69	—	43
PB14MCS-36-125	—	1 1/2	3 13/16	6F	36	6.316	6.206	6.816	1.08	5.61	5.3	—	6.69	—	45
PB14MCS-37-125	—	1 1/2	4 1/8	6F	37	6.492	6.382	7.167	1.08	5.61	5.63	—	6.69	—	49
PB14MCS-38-125	—	1 1/2	4 1/8	6F	38	6.667	6.557	7.167	1.08	5.61	5.63	—	6.69	—	51
PB14MCS-39-125	—	1 1/2	4 3/8	6F	39	6.842	6.732	7.518	1.08	5.61	5.89	—	6.69	—	54
PB14MCS-40-125	—	1 1/2	4 3/8	6F	40	7.018	6.908	7.518	1.08	5.61	5.89	—	6.69	—	57
PB14MCS-43-125	—	1 1/2	4 13/16	6F	43	7.544	7.434	8.395	1.2	5.61	6.51	—	6.81	—	68
PB14MCS-45-125	—	1 1/2	5	6F	45	7.895	7.785	8.395	1.2	5.61	6.76	—	6.81	—	75
PB14MCS-48-125	—	1 1/2	5 5/8	6F	48	8.421	8.311	8.941	1.2	5.61	7.29	—	6.81	—	86
B14MCS-50-125	4535	1 15/16	4 15/16	A1F	50	8.772	8.662	9.292	—	5.61	—	7.44	3.5	2.11	38
B14MCS-53-125	4535	1 15/16	4 15/16	A1F	53	9.299	9.189	9.687	—	5.61	—	7.83	3.5	2.11	46
B14MCS-56-125	4535	1 15/16	4 15/16	A1F	56	9.825	9.715	10.355	—	5.61	—	8.35	3.5	2.11	54
B14MCS-60-125	4535	1 15/16	4 15/16	A1F	60	10.527	10.417	11.067	—	5.61	—	9.06	3.5	2.11	64
B14MCS-63-125	4535	1 15/16	4 15/16	A1F	63	11.053	10.943	11.750	—	5.61	—	9.59	3.5	2.11	73
B14MCS-67-125	4535	1 15/16	4 15/16	A1F	67	11.755	11.645	12.500	—	5.61	—	9.88	3.5	2.11	88
B14MCS-71-125	5040	2 7/16	5	A1F	71	12.457	12.347	13.187	—	5.61	—	10.67	4	1.61	103
B14MCS-75-125	5040	2 7/16	5	A1F	75	13.158	13.048	13.730	—	5.61	—	11.63	4	1.61	117
B14MCS-80-125	5040	2 7/16	5	A1F	80	14.036	13.926	14.625	—	5.61	—	12.59	4	1.61	136
B14MCS-90-125	5040	2 7/16	5	D1	90	15.790	15.68	—	—	5.61	10	14.26	4	1.61	135
B14MCS-112-125	6050	4 7/16	5 15/16	A1	112	19.650	19.54	—	—	5.61	—	16.35	5	.61	317
B14MCS-140-125	6050	4 7/16	5 15/16	D3	140	24.562	24.452	—	—	5.61	15.5	20.74	5	.61	373
B14MCS-168-125	7060	4 15/16	7	C3	168	29.475	29.365	—	—	5.61	17	25.11	6	.39	524
B14MCS-180-125	7060	4 15/16	7	C3	180	31.580	31.470	—	—	5.61	17	27.06	6	.39	567
B14MCS-200-125	7060	4 15/16	7	C3	200	35.089	34.979	—	—	5.61	17	30.29	6	.39	648
B14MCS-224-125	7060	4 15/16	7	C3	224	39.300	39.190	—	—	5.61	17	34.21	6	.39	753

NOTE — Numerals in Type Designations mean: 1 = Solid, 2 = Web, 3 = Arm Construction; F = Flanged Sprocket.