

## Dual Lock Quick-Acting Couplings with Ferrule

## Features:

- working pressure: **300 PSI** at ambient temperature (70°F)
- trivalent chrome plated coupling with plated steel ferrule
- also available in brass and stainless steel
- for crimp recommendations see page 838
- 3/8" and 1" sizes available upon request, contact Dixon



Body Size	Hose ID	Hose OD		Part #	Price/E
		From:	To:		
1/2"	1/2"	54/64"	1-2/64"	<b>PHL8WF</b>	<b>\$42.00</b>
1/2"	3/4"	1-10/64"	1-22/64"	<b>PHL12WF</b>	<b>43.95</b>

F

## Dual Lock Quick-Acting Couplings with Knurled Flanged Sleeve

## Features:

- large, raised collar sleeve permits easier handling when wearing gloves
- trivalent chrome plated steel



## Hose End Barb with Knurled Flanged Sleeve

Body Size	Hose ID Size	Part #	Price/E	Opt Qty
1/2"	3/8"	<b>PHL6FS</b>	<b>\$38.99</b>	25
1/2"	1/2"	<b>PHL8FS</b>	<b>38.99</b>	25
1/2"	3/4"	<b>PHL12FS</b>	<b>40.98</b>	25

## Male Pipe Thread with Knurled Flanged Sleeve



Body Size	Male NPT	Part #	Price/E	Opt Qty
1/2"	3/8"	<b>PML6FS</b>	<b>\$37.09</b>	25
1/2"	1/2"	<b>PML8FS</b>	<b>36.91</b>	25
1/2"	3/4"	<b>PML12FS</b>	<b>36.91</b>	25

## Female Pipe Thread with Knurled Flanged Sleeve



Body Size	Female NPT	Part #	Price/E	Opt Qty
1/2"	1/2"	<b>PFL8FS</b>	<b>\$41.72</b>	25
1/2"	3/4"	<b>PFL12FS</b>	<b>41.72</b>	25

## Dual Y Valves

## Features:

- dual action valve, ideal for compressor applications
- pressure rating:
  - non-vented: **600 PSI** WOG
  - vented: **125 PSI** CWP (Cold Working Pressure)



vented

## Non-Vented

Female NPT Inlet (1)	Female NPT Outlets (2)	Brass	
		Part #	Price/E
1"	3/4"	<b>BBV100DW</b>	<b>\$163.90</b>
1 1/4"	3/4"	<b>BBV125DW</b>	<b>163.90</b>

## Vented

Female NPT Inlet (1)	Female NPT Outlets (2)	Brass	
		Part #	Price/E
1"	3/4"	<b>BBV100DWV</b>	<b>\$163.90</b>
1 1/4"	3/4"	<b>BBV125DWV</b>	<b>163.90</b>