

Plain Wye with Pin Lugs

04-106

Feature:

- divides one stream into two



Inlet Female	(2) Outlets Male	Cast Brass Part #	Price	Wt. Lbs.
1½" NST (NH)	1½" NST (NH)	PW15F15F	\$200.00	3.0
1½" NPSH	1½" NPSH	PW15S15S	200.00	3.0
1½" CT	1½" CT	PW15_15 ¹	POR	3.0
2½" NST (NH)	1½" NST (NH)	PW25F15F	225.00	5.5
2½" CT	1½" NPSH	PW25_15S ¹	POR	5.5
2½" CT	1½" NST (NH)	PW25_15F ¹	POR	5.5
2½"	2½"	PW25F25F	250.00	6.8
2½" CT	2½" CT	PW25_25 ¹	POR	6.8

¹ Customer Thread (*must specify*) refer to legend on page 566

Hydrant Diffusers

Features:

- powder coated red finish
- brass swivels with full 360° rotation
- flow can be directed to your desired position while flushing the hydrant
- specially designed outlet reduces high velocity discharge to a slower diffused pattern protecting landscape and traffic



Female NST (NH)	Carbon Steel Part #	Price	Wt. Lbs.
2½"	HD250F	\$1492.00	14
4"	HD400F	3906.00	26
4½"	HD450F	4000.00	26

Single Hydrant Gate Valves with Handwheel

Application:

- protects fire hydrants from damage that can occur if they are used for throttling

Features:

- pin lug swivel, non-rising stem, red handwheel
- metal to metal seal
- U/L listed
- for use on hydrants, standpipes, and fire pumps
- maximum operating pressure: **300 PSI** (water only) at 70°F (21°C)



Inlet Female	Outlet Male	Forged Brass Part #	Price	Wt. Lbs.
2½" NST (NH)	2½" NST (NH)	HGVW250F	\$643.65	8.7
2½" NYFD	2½" NYFD	HGVW250NYFD	680.00	8.7

Replacement Part

Description	Part #	Price	Wt. Lbs.
handwheel	HGVW250-W	\$43.00	.35

P