


## Wilkerson High Pressure Compact Regulators



**Features:**

- 0-250 PSI adjusting range
- self-relieving standard
- non-rising push/pull locking adjustment knob
- panel mount nut standard
- excellent flow characteristics
- can be installed with the adjusting knob in any position
- two 1/4" NPT gauge ports standard on models without gauge, one 1/4" NPT gauge port standard on models with gauge - can be used for additional outlet ports
- models supplied without gauge use a GC240 gauge
- maximum operating conditions:  
**300 PSIG (20.7 bar) and 32°F to 150°F (0°C to 65.5°C)**

F

Size	Flow (SCFM)	With Gauge		Without Gauge	
		Part #	Price/E	Part #	Price/E
1/4"	71.5	<b>R16-02RHG</b>	<b>\$120.25</b>	<b>R16-02RH</b>	<b>\$99.55</b>
3/8"	80.5	<b>R16-03RHG</b>	<b>120.25</b>	<b>R16-03RH</b>	<b>99.55</b>
1/2"	88.0	<b>R16-04RHG</b>	<b>120.25</b>	<b>R16-04RH</b>	<b>99.55</b>

## Wilkerson High Pressure Standard Regulators


**Features:**

- 0-250 PSI adjusting range
- self-relieving standard
- non-rising push/pull locking adjustment knob
- panel mount nut standard
- excellent flow characteristics
- can be installed with the adjusting knob in any position
- two 1/4" NPT gauge ports standard on models without gauge, one 1/4" NPT gauge port standard on models with gauge - can be used for additional outlet ports
- models supplied without gauge use a GC240 gauge
- maximum operating conditions:  
**300 PSIG (20.7 bar) and 32°F to 150°F (0°C to 65.5°C)**

Size	Flow (SCFM)	With Gauge		Without Gauge	
		Part #	Price/E	Part #	Price/E
1/4"	112	<b>R26-02RHG</b>	<b>\$172.40</b>	<b>R26-02RH</b>	<b>\$151.70</b>
3/8"	148	<b>R26-03RHG</b>	<b>172.40</b>	<b>R26-03RH</b>	<b>151.70</b>
1/2"	185	<b>R26-04RHG</b>	<b>172.40</b>	<b>R26-04RH</b>	<b>151.70</b>

See pages 229-231 for regulator accessories.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure.