

Notched Cam and Groove

Features:

- coupling can be removed from a damaged hose by cutting away the ferrule, without necessarily damaging the fitting, *after inspection of the fitting to determine its suitability for reuse*, it can be reinstalled into another hose by using a *new ferrule*
- system allows you to better manage your inventories, you can stock one coupling and two ferrules, and cover the same hose range with less inventory, *you must purchase a fitting and the matching ferrule to create an assembly*
- for use with notched ferrules on previous page



Dixon stems and ferrules are specifically designed to be used together as a coupling system. Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturer's stems or ferrules with Dixon products.

Couplers

EZ Boss-Lock type C with notched shank



female coupler x notched hose shank


Size	316 Stainless Steel	
	Part #	Price/E
1½"	RC150EZNO	\$113.75
2"	RC200EZNO	121.30
3"	RC300EZNO	208.20
4"	RC400EZNO	310.85

Boss-Lock type C with notched shank




female coupler x notched hose shank

Size	316 Stainless Steel	
	Part #	Price/E
1½"	RC150BLNO	\$118.00
2"	RC200BLNO	116.80
3"	RC300BLNO	199.40
4"	RC400BLNO	297.00



crimped assembly

Contact Dixon for swage and crimp recommendations.



swaged assembly

Adapters

Boss-Lock type E with notched shank



male adapter x notched hose shank

Size	316 Stainless Steel	
	Part #	Price/E
1½"	RE150NO	\$61.00
2"	RE200NO	65.30
3"	RE300NO	126.00
4"	RE400NO	246.90



swaged assembly

Contact Dixon for swage and crimp recommendations.



crimped assembly