

Elbows Angle and Suction

Features:

- for use on pump discharge valves, or suction inlets to minimize hose kinking
- rocker lug swivel
- satin brass finish
- -C polished chrome plated

Male NST (NH)	Female NST (NH)	Angle	Brass Part #	Wt. Lbs	Price/E
2½"	2½"	30°	RSE30250F-C NEW	4.48	\$298.00
2½"	2½"	45°	RSE45250F	4.48	270.00
2½"	2½"	45°	RSE45250F-C	4.48	298.00
2½"	2½"	90°	RSE90250F	4.66	216.00
2½"	2½"	90°	RSE90250F-C	4.66	242.00



30° elbow



45° elbow

Continuous Swivel

Features:

- allows hose to swing when connected
- full waterway reduces friction loss
- short style radius is 2½" measured from the center of the waterway to the end of the discharge thread

Female NPT	Male Thread	Length	Cast Brass Part #	Wt. Lbs	Price/E
1½"	1½" NST (NH)	2½"	CSES150F	4.00	\$180.00
2"	1½" NST (NH)	2½"	CSES2015F	3.75	180.00
1½"	1½" NPT	2½"	CSES150T	4.00	180.00



Dixon Northline Adapters N54 - Angle and Suction Elbows

Features:

- ideal for fire apparatus with front suction connections
- anodized, powder coated aluminum, extruded
- anodized female swivel connections

Angle	Male NST (NH)	Female NST (NH) Swivel	Aluminum Part #	Wt. Lbs	Price/E
30°	2½"	2½"	N5430-25F25F	2.0	\$223.95
45°	2½"	2½"	N5445-25F25F	2.0	223.95
60°	2½"	2½"	N5460-25F25F	2.0	235.30
90°	2½"	2½"	N5490-25F25F	2.0	272.65



90° elbow



Push Pull Drain Valve

Features:

- direct mount
- 2½" handle length

Female Inlet	Female Outlet	Brass Part #	Price	Wt. Lbs.
¾" NPT	¾" NPT	PPDV75	\$58.05	1.10

