Fire-Rated Poke-Throughs



SystemOne Recessed 8 Inch Sub-Plates

Center Plate Configurations


- Allows for 3 duplexes or up to 18 data/ AV jacks. Other combinations possible
- Accepts third party AV devices (i.e. Extron[®], Crestron[®], FSR[®])
- Standard NEMA spacing between devices



Center Sub-Plates - Single Gang

Center Sub-Plates - Single Gang					
Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate		
Blank cover plate	•	(2) Extron® MAAP openings			
S1R8CSPB	•	S1R8CSPC	•		
(1) 1 unit Hubbell iSTATION opening	i	(1) 1.5 unit Hubbell iSTATION opening (See section W for modules)			
S1R8CSPD	2	S1R8CSPE			
(1) 1.60" opening for 20A & 30A Twist-Lock®		(1) Duplex opening	÷		
S1R8CSPG	9	S1R8CSPI	•		
(1) 1.40" opening for simplex or 15A Twist-Lock®	i i	(1) Style Line® Decorator opening	ò		
S1R8CSPJ	•	S1R8CSPK	•		

Center Sub-Plates - Two and Three Gang



Note: Rectangle sub-plates are for center compartment, crescent sub-plates are for perimeter compartments and are not inter-changeable See page P-8 for Covers and Accessories.

Extron® is a registered trademark of Extron Electronics. Crestron® is a registered trademark of Crestron Electronics, Inc. FSR® is a registered trademark of FSR Inc.

Perimeter Plate Configurations

- Available in pre-wired duplexes or openings to accommodate third party AV Devices
- Multiple duplexes can be wired in the supplied junction box or independently



Perimeter Sub-Plates

Description/Cat. No.	Sub-plate	Description/Cat. No.	Sub-plate
Blank cover plate		Single Extron® AAP opening	Ċ
S1R8PSPU		S1R8PSPV	•
Pull through with 1" bushing opening	0	Single Extron® AAP opening	
S1R8PSPW		S1R8PSPX	
(1) 1 unit Hubbell iSTATION opening (See section W for modules)		Dual 20A pre-wired power cubes; one circuit (Supplied with isolated ground sticker)	
S1R8PSPY		S1R8PSPZ	
Dual 20A pre-wired power cubes; one circuit (Supplied with isolated ground sticker); Marked with "⑤ Controlled"		\$1R8P\$PZ25 (25 Inch leads)	
S1R8PSPZC			