

Strap-Grip Saddles and Male Stems



Features:

- designed to provide greater resistance to end pull than conventional band clamps
- male fittings are designed for use with Strap-Grip saddles
- cam and groove fittings are available, see page 70
- Saddles are designed for use with $\frac{3}{4}$ " or $\frac{5}{8}$ " wide bands. A band clamp should first be applied to OD to seal the hose in sizes 3" and over. Then Strap-Grip saddles should be banded on top of initial clamps to anchor the fitting in the hose.

saddles

Size	Hose OD		Plated Iron	
	from	to	Part #	Price/pair ¹
1½"	1-13/16"	2-1/8"	SGS150	\$14.40
2"	2-5/8"	3"	SGS200	16.90
3"	3-1/2"	3-7/8"	SGS300	21.40
4"	4-9/16"	5-1/8"	SGS400	24.40
6"	6-1/2"	7-1/16"	SGS600	45.00

¹ prices are for two saddles



male NPT x hose shank

schedule 40

Size	Plated Carbon Steel		Stainless Steel	
	Part #	Price/pair	Part #	Price/E
1½"	LP21	\$60.00	---	---
2"	LP26	53.20	---	---
3"	LP36	125.00	RLP36 ¹	\$221.40
4"	LP46	164.00	RLP46 ¹	375.00
6"	LP66	340.00	---	---

schedule 80 ²

Size	Plated Carbon Steel	
	Part #	Price/E
1½"	LP21-80	\$69.00
2"	LP26-80	71.85

¹ made from tubular steel

² schedule 80 stems meet NFPA 58



K