
# MSHA Approved Mine Fire Hose

#### Specifications:

 approved by MSHA: Mine Safety and Health Administration for all mine fire protection applications

## Single Jacket

#### Features:



· tube construction: flame resistant lining

proof pressure: **500 PSI** at 70°F (21°C)

service test pressure: 250 PSI at 70°F (21°C)

working pressure: 225 PSI at 70°F (21°C)

### Coupled with female and male aluminum rocker lug expansion ring couplings

Size	Length	Thread	Part #	Price
1½"	50'	NST (NH)	SM515W50RAF	\$561.05
1½"	50'	NPSH	SM515W50RAS	561.05

## **Double Jacket**

#### Features:

- outer construction: double jacket, synthetic flame resistant
- tube construction: flame resistant lining
- proof pressure: 800 PSI at 70°F (21°C)
- service test pressure: 400 PSI at 70°F (21°C)
- working pressure: 360 PSI at 70°F (21°C)

## Coupled with female and male aluminum rocker lug expansion ring couplings

Size	Length	Thread	Part #	Price
1½"	50'	NST (NH)	DM815W50RAF	\$660.00
1½"	50'	NPSH	DM815W50RAS	660.00

## Double Jacket Potable Water Hose - Blue

#### Features:

- outer construction: double jacket, all polyester
- tube construction: thermoplastic
- proof pressure: 600 PSI at 70°F (21°C)
- service test pressure: 300 PSI at 70°F (21°C)
- working pressure: 270 PSI at 70°F (21°C)

### Coupled with female and male thread, rocker lug, brass expansion ring couplings

Size	Length	Thread	<i>Brass</i> Part #	Price/E	<i>Aluminum</i> Part #	Price/E
1½"	50'	NPSH	PW615B50RBS	\$514.75	PW615B50RAS	\$440.70
1½"	100'	NPSH	PW615B100RBS	840.00	PW615B100RAS	752.35
1½"	50'	NST (NH)	PW615B50RBF	514.75	PW615B50RAF	440.70
1½"	100'	NST (NH)	PW615B100RBF	840.00	PW615B100RAF	752.35
2½"	50'	NPSH	PW625B50RBS	926.45	PW625B50RAS	729.70
2½"	100'	NPSH	PW625B100RBS	1493.15	PW625B100RAS	1297.00
2½"	50'	NST (NH)	PW625B50RBF	926.45	PW625B50RAF	729.70
21/2"	100'	NST (NH)	PW625B100RBF	1493.15	PW625B100RAF	1297.00

DPL714







