

Large Capacity Low Pressure / Gravity Nozzle



Application:

rugged utility nozzle for low pressure/gravity applications

Features:

- rapid flow due to 1¼" oversize design
- maximum operating pressure: **25 PSI**

| Female NPT Inlet | Spout Outlet | Aluminum Part # | Price/E |
|------------------|--------------|-----------------|-----------------|
| 1¼" | 1¼" | 1250-94 | \$259.30 |

repair kits

| Description | Part # | Price/E |
|---|---------------|------------|
| trigger, pin | 1250TK | POR |
| plunger, O-rings, valve seal, valve base, valve plate | 1250SK | POR |

Hose Swivels

Features:

- for use with petroleum and home heating oil hose
- prevents hose twisting or kinking

Hose Shank



| Male NPT | Shank Size | Bronze Part # | Price/E |
|----------|------------|---------------|-----------------|
| 1½" | 1½" | 1565U | \$153.20 |

repair kit

| Description | Part # | Price/E |
|---|---------------|------------|
| replacement seal kit and retaining ring | 1500SK | POR |

Heavy Duty

Features:

- male NPT x female NPT threaded connections
- heavy duty internal thrust bearing and anti-friction seal design ensures swiveling at **-40°F**
- can be lubricated without disassembly by using the optional grease fitting kit



| Male NPT | Female NPT | Aluminum Part # | Price/E |
|----------|------------|-----------------|-----------------|
| 1¼" | 1¼" | SWMF125 | \$204.70 |
| 1½" | 1½" | SWMF150 | 204.70 |
| 2" | 2" | SWMF200 | 228.75 |

repair kits

| Description | Part # | Price/E |
|-----------------------------|------------------|----------------|
| swivel grease nipple kit | SWMF-RK1 | \$16.25 |
| swivel seal and wear kit | SWMF-RK2 | 54.25 |
| complete swivel rebuild kit | SWMF-RK3 | 118.80 |
| swivel seal and wear kit | SWMF-RK22 | 32.05 |
| complete rebuild kit | SWMF-RK32 | 117.25 |

Hose Swivels

Features:

- Allows the hose to relax to it's natural rest position while allowing freedom of movement without adding torque stress at the point of connection.
- simple design, low maintenance - consists of 2 body halves, ball bearings and a washer
- male NPT x female NPT threaded connections
- FKM seals standard, Chemraz® and Kalrez® optional
- working pressure: **150 PSI**
- maximum temperature: **300°F (149°C)**



| Size | 316 Stainless Steel | | Aluminum | |
|------|---------------------|-----------------|----------------|-----------------|
| | Part # | Price/E | Part # | Price/E |
| ¾" | HS075SS | \$684.45 | HS075AL | \$315.60 |
| 1" | HS100SS | 684.45 | HS100AL | 315.60 |
| 1½" | HS150SS | 713.60 | HS150AL | 370.55 |
| 2" | HS200SS | 713.60 | HS200AL | 370.55 |
| 3" | HS300SS | 1513.10 | HS300AL | 876.30 |
| 4" | HS400SS | 2926.25 | HS400AL | 1695.40 |

S