

## TYPE 4X, 12

Rating					Watertight Devices				Accessories			Replacement Interiors	
Amps	Poles and Wires	Configuration Recept./ Conn.	Plug/ Inlet	AC Voltage	Receptacle	Plug	Connector	Inlet	Back Boxes Non-Metallic	Back Boxes Metallic*	Closure Caps	Recept./ Conn.	Plug/ Inlet
16	2P 3W			100-130V									
20	2P 3W			125V									
16/20	2P 3W			220-240V 250V									
20	2P 3W			480V									
20	3P 4W			125/250V									
16/20	3P 4W			380-415V									
	3P 4W			3Ø 250V									
20	3P 4W			3Ø 480V									
20	3P 4W			3Ø 600V									
16/20	4P 5W			220/380V 240/415V									
	4P 5W			3ØY 120/208V									
20	4P 5W			3ØY 277/480V									
20	4P 5W			3ØY 347/600V									
30	2P 3W			125V									
30/32	2P 3W			220-240V 250V									
30	2P 3W			480V									
30	3P 4W			125/250V									
30/32	3P 4W			380-415V									
	3P 4W			3Ø 250V									
30	3P 4W			3Ø 480V									
30	3P 4W			3Ø 600V									
30/32	4P 5W			220/380V 240/415V									
	4P 5W			3ØY 120/208V									
30	4P 5W			3ØY 277/480V									
30	4P 5W			3ØY 347/600V									
32	2P 3W			100-130V									
32	3P 4W			380V 50Hz 440V 60Hz									

Note: See page G-14 and G-15 for back boxes and accessories, G-16 and G-17 for product dimensions, G-18 and G-19 for product specifications and HP ratings.

See page G-15 for closure caps, purchased separately. PC320, PC420, PC520, PC3430, PC530 are not UL or CSA.

\*These boxes are cast aluminum, suitable for IP54 requirements and are finished with enamel paint.

†Consult factory.

See 20, 30, 60 & 100 amp offering for additional dual rated devices for use at either 16A or 20A, 30A or 32A, 60A or 63A and 100A or 125A.