

Straight Blade Devices
15A, 125V, 2 Pole, 3 Wire Grounding
Miscellaneous Receptacles

HUBBELL

Ordering Information

| | | | |
|---|-----------------------|---------------------|-----------------------------|
| Description Replacement receptacle for HBL5236 | Device Color Brown | UPC 783585014562 | Catalog Number HBL5236M2 |
|---|-----------------------|---------------------|-----------------------------|

Listings

UL Listed to UL498 File E2186
Certified to CSA, C22.2, No. 42 file 285
NEMA® WD-6 Compliant

Specifications

| | |
|----------------|-------------------|
| Face | Phenolic |
| Base | Phenolic |
| Power Contacts | .032" (.81) Brass |

Performance

Electrical

Current Interrupting Certified for current interrupting at full rated current
Dielectric Voltage Withstands 2,000V minimum

Mechanical

Product Identification Ratings are a permanent part of the device
Terminal Accommodation #14-#10 AWG copper stranded or solid conductor only
Terminal Identification Terminals identified in accordance with UL 498 and CSA

Environmental

Flammability UL 94 V-2 or better
Operating Temperatures Maximum continuous 75°C; minimum -40°C (w/o impact)



Resources

[eCatalog](#)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

