

## Features and Benefits

### inREACH™ Industrial Weatherproof Cord Reels

- UL Type 4
- 600V AC, SOW Type Cable
- Durable, corrosion resistant cast aluminum construction design with yellow or white powder coat finish
- Multi-position guide arm
- Positive-latch mechanism automatically maintains desired cord length
- 16–10 AWG, 3 & 4 conductor cord for greater current carrying capacity



HBLW45103

### inREACH™ Industrial Weatherproof Cord Reels



HBLW45163W



HBLW35143



HBLW45103

Description	Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight Lbs. (kg)	Yellow Reel	White Reel
Weatherproof Industrial Reel	10	600	45 (13.7)	16/3 SOW	23.6 (10.7)	<b>HBLW45163</b>	<b>HBLW45163W</b>
				16/4 SOW	25.6 (11.6)	<b>HBLW45164</b>	<b>HBLW45164W</b>
	35 (10.7)	16/3 SOW	22.5 (10.2)	<b>HBLW35163</b>	<b>HBLW35163W</b>		
		16/4 SOW	23.1 (10.5)	<b>HBLW35164</b>	<b>HBLW35164W</b>		
	25 (7.6)	16/3 SOW	21.4 (9.7)	<b>HBLW25163</b>	<b>HBLW25163W</b>		
		16/4 SOW	21.8 (9.9)	<b>HBLW25164</b>	<b>HBLW25164W</b>		
Weatherproof Industrial Reel	15	600	45 (13.7)	14/3 SOW	28.2 (12.8)	<b>HBLW45143</b>	<b>HBLW45143W</b>
				14/4 SOW	30.0 (13.6)	<b>HBLW45144</b>	<b>HBLW45144W</b>
	35 (10.7)	14/3 SOW	25.1 (11.4)	<b>HBLW35143</b>	<b>HBLW35143W</b>		
		14/4 SOW	26.5 (12.0)	<b>HBLW35144</b>	<b>HBLW35144W</b>		
	25 (7.6)	14/3 SOW	22.5 (10.2)	<b>HBLW25143</b>	<b>HBLW25143W</b>		
		14/4 SOW	24.3 (11.0)	<b>HBLW25144</b>	<b>HBLW25144W</b>		
Weatherproof Industrial Reel	20	600	45 (13.7)	12/3 SOW	31.3 (14.2)	<b>HBLW45123</b>	<b>HBLW45123W</b>
				12/4 SOW	32.2 (14.6)	<b>HBLW40124</b>	<b>HBLW40124W</b>
	35 (10.7)	12/3 SOW	28.9 (13.1)	<b>HBLW35123</b>	<b>HBLW35123W</b>		
		12/4 SOW	30.6 (13.9)	<b>HBLW35124</b>	<b>HBLW35124W</b>		
	25 (7.6)	12/3 SOW	24.9 (11.3)	<b>HBLW25123</b>	<b>HBLW25123W</b>		
		12/4 SOW	27.6 (12.5)	<b>HBLW25124</b>	<b>HBLW25124W</b>		
Weatherproof Industrial Reel	30	600	40 (12.2)	10/3 SOW	33.3 (15.1)	<b>HBLW40103</b>	<b>HBLW40103W</b>
			35 (10.7)	10/3 SOW	31.7 (14.4)	<b>HBLW35103</b>	<b>HBLW35103W</b>
				10/4 SOW	34.2 (15.5)	<b>HBLW35104</b>	<b>HBLW35104W</b>
25 (7.6)	10/3 SOW	28.4 (12.9)	<b>HBLW25103</b>	<b>HBLW25103W</b>			
				10/4 SOW	30.2 (13.7)	<b>HBLW25104</b>	<b>HBLW25104W</b>

### inREACH™ Accessories

Description	Weight Lbs. (kg)	Catalog Number
Mounting bracket	2.5 (1.1)	<b>HBLIMB</b>
340° pivot base	3.5 (1.1)	<b>HBLI340PB</b>
Replacement stop.	.2 (.09)	<b>HBLI16BS</b>
		<b>HBLI14BS</b>
		<b>HBLI12BS</b>
		<b>HBLI10BS</b>

### Labor Savings are inREACH™!



HBLI340PB



HBLI16BS



Dimensions in Inches (mm)