

SR1430 -- Range and Dryer Receptacles



SR1030

SelectSpec light industrial, commercial and hospital grade receptacles are ideal for any project where ease of wiring, durability and reliability are required. The impact resistant nylon face is available in a variety of colors to blend into the décor of office buildings, administrative areas, schools, government facilities and retail spaces.

Product Specifications

SELECTSPEC Product Type	Straight Blade Products
Straight Blade Product	Dryer Receptacle
Straight Blade Product Grade	Commercial to Light Industrial
Straight Blade Product Style	Flush Mount, Back Wired
Straight Blade Receptacle Rating	30A, 125/250V
Straight Blade Receptacle Wiring Scheme	3 Pole, 4 Wire Non-Grounding
Straight Blade NEMA Configuration	14-30R
Straight Blade Receptacle Color	Black
Straight Blade Listings and Approvals	UL Listed
Features	Multiple Drive Screws, Pre-Tensioned Ground Contacts, Large Oxide Cutting Terminal Screws, Brass Alloy Triple Wipe Power Contacts
Face	Heat and Impact Resistant Reinforced Thermoplastic Polyester
Base	Heat and Impact Resistant Reinforced Thermoplastic Polyester
Contacts/Blade Material	Tin Plated Brass
Mounting Yoke	Steel-Zinc Plated
Dielectric Voltage	Withstands 2,000V Minimum
Max Working Voltage	250V AC or DC
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30 deg C temperature rise at full rated current after 50 cycles of overload at 150% of rated direct current.
Terminal Identification	Terminals identified in accordance with UL 498 (Brass, White, Green).
Terminal Accommodation	#14 to #10 AWG Copper Conductors Only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94V2
Operating Temperatures	Maximum Continuous: 60 deg C, minimum: -40 deg C. (w/o impact).
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

