

## SR620G -- Single Receptacles



SelectSpec light industrial, commercial and hospital grade receptacles are ideal for any project where ease of wiring, durability and reliability are required. The impact resistant nylon face is available in a variety of colors to blend into the décor of office buildings, administrative areas, schools, government facilities and retail spaces.

### Product Specifications

<b>SELECTSPEC Product Type</b>	Straight Blade Products
<b>Straight Blade Product</b>	Single Receptacle
<b>Straight Blade Product Grade</b>	Commercial to Light Industrial
<b>Straight Blade Product Style</b>	Flush Mount, Back Wired
<b>Straight Blade Receptacle Rating</b>	20A, 250V
<b>Straight Blade Receptacle Wiring Scheme</b>	2 Pole, 3 Wire Grounding
<b>Straight Blade NEMA Configuration</b>	6-20R
<b>Straight Blade Receptacle Color</b>	Gray
<b>Straight Blade Listings and Approvals</b>	UL Listed Fed Spec
<b>Features</b>	Multiple Drive Screws, Pre-Tensioned Ground Contacts, Large Oxide Cutting Terminal Screws, Brass Alloy Triple Wipe Power Contacts
<b>Face</b>	Nylon
<b>Base</b>	Thick Walled High Impact Resistant Nylon
<b>Contacts/Blade Material</b>	Brass Alloy
<b>Mounting Yoke</b>	Steel-Zinc Plated
<b>Dielectric Voltage</b>	Withstands 2,000V Minimum
<b>Max Working Voltage</b>	250V AC or DC
<b>Current Interrupting</b>	Certified for current interrupting at full rated current.
<b>Temperature Rise</b>	Max 30 deg C temperature rise at full rated current after 50 cycles of overload at 150% of rated direct current.
<b>Terminal Identification</b>	Terminals identified in accordance with UL 498 (Brass, White, Green).
<b>Terminal Accommodation</b>	#14 to #10 AWG Copper Conductors Only.
<b>Product Identification</b>	Ratings are a permanent part of the device.
<b>Flammability</b>	UL 94V2
<b>Operating Temperatures</b>	Maximum Continuous: 60 deg C, minimum: -40 deg C. (w/o impact).
<b>Link to Drawing Library</b>	<a href="#">Click here for Library</a>
<b>Link to PDF Catalog</b>	<a href="#">Click here for Catalog</a>

