

# Locking Devices Insul-Lock Plus Devices 20A Panel Mount

# HUBBELL

## Features

- Impact resistant thermoplastic construction
- Panel mount devices accept commonly available .25" flat tab style connectors
- UL Enclosure type 4X and IP65 rated
- Disconnectable under load
- Industry standard mating

## Ordering Information

<b>Description</b> Outlet, 1/4" tab terminations with divider	<b>UPC</b> 783585580906	<b>Catalog Number</b> HBLFPD
<b>Termination</b> .25" flat tab style connectors	<b>Color</b> Black and Yellow	

## Listings

cULus  
UL50E Encl. type 4X when used in combination with covers HBLFPC or HBLFPDC  
or with when mated to HBLMC  
IP65 rated when used in combination with covers HBLFPC or HBLFPDC or with  
when mated to HBLMC

## Specifications

Body	Thermoplastic
Contacts	Copper Alloy
Weight	0.1

## Performance

<b>Electrical</b>	
Amperage	20A
Voltage	up to 250V AC



Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

