

Charging Solutions Power Charging Station

15A Combination Wireless Wall Mount Charger & USB Outlet

HUBBELL

Features

- Qi certified
- No need for cables
- Dual coils for optimum phone positioning
- Secure phone holder

Ordering Information

Description	Color	UPC Number	Catalog Number
Combination Wireless Wall Mount Charger & USB Outlet	White	883778309434	USB1528AC

Listings

cULus UL 1310, UL 498
FCC Part 15

Specifications

Face	Reinforced Thermoplastic
Base	Reinforced Thermoplastic
LED	Green/Blue Indicator
Terminal Screws	Plated Steel
Mounting Screws	Zinc Plated Steel
USB Ports	Stainless Steel, 10,000 cycles, Type A+C

Performance

Electrical

Qi Rating	Certified 7.5 Watts
Input Voltage	125V
Receptacle	15A, 125V, Tamper-Resistant
USB	5A, 5V
Dielectric Voltage	Withstands 1,500V minimum Complies with USB BC1.2 Battery Charging and 3.0 Power Delivery Specifications

Mechanical

Product Identification Terminal Accommodation	Ratings are a permanent part of the device #14-#10 AWG copper stranded or solid conductor only
Terminal Identification	Terminals identified in accordance with UL 498 and CSA

Environmental

Flammability	UL 94V-2
Operating Temperature	Maximum continuous 75°C, minimum -40°C (w/o impact)



Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

